



MRD 6000

4K UHD Receiver Decoder

User Manual



Copyright

© 2018 Sencore, Inc. All rights reserved.
3200 Sencore Drive, Sioux Falls, SD USA
www.sencore.com

This publication contains confidential, proprietary, and trade secret information. No part of this document may be copied, photocopied, reproduced, translated, or reduced to any machine-readable or electronic format without prior written permission from Sencore. Information in this document is subject to change without notice and Sencore Inc. assumes no responsibility or liability for any errors or inaccuracies. Sencore, Sencore Inc, and the Sencore logo are trademarks or registered trademarks in the United States and other countries. All other products or services mentioned in this document are identified by the trademarks, service marks, or product names as designated by the companies who market those products. Inquiries should be made directly to those companies. This document may also have links to third-party web pages that are beyond the control of Sencore. The presence of such links does not imply that Sencore endorses or recommends the content on those pages. Sencore acknowledges the use of third-party open source software and licenses in some Sencore products. This freely available source code can be obtained by contacting Sencore Inc.

About Sencore

Sencore is an engineering leader in the development of high-quality signal transmission solutions for the broadcast, cable, satellite, IPTV, telecommunications, and professional audio/video markets. The company's world-class portfolio includes video delivery products, system monitoring and analysis solutions, and test and measurement equipment, all designed to support system interoperability and backed by best-in-class customer support. Sencore meets the rapidly changing needs of modern media by ensuring the efficient delivery of high-quality video from the source to the home. For more information, visit www.sencore.com.

Revision History

Date	Version	Description	Author
11/06/2018	1.0	MRD 6000 Manual – First Draft	GAK

Safety Instructions

- Read these instructions
- Keep these instructions
- Heed all warnings
- Follow all instructions
- Do not use this apparatus near water
- Clean only with dry cloth
- Do not block any ventilation openings. Install in accordance with the manufacturer's instructions
- Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat
- Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade or the third prong is provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.
- Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.
- Only use attachments/accessories specified by the manufacturer.
- Unplug this apparatus during lightning storms or when unused for long periods of time.
- Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.
- Do not expose this apparatus to dripping or splashing and ensure that no objects filled with liquids, such as vases, are placed on the apparatus.
- To completely disconnect this apparatus from the AC Mains, disconnect the power supply cord plug from the AC receptacle.
- The mains plug of the power supply cord shall remain readily operable.
- **Damage Requiring Service:** Unplug this product from the wall outlet and refer servicing to qualified service personnel under the following conditions:
 - When the power-supply cord or plug is damaged.
 - If liquid has been spilled, or objects have fallen into the product.
 - If the product has been exposed to rain or water.
 - If the product does not operate normally by following the operating instructions. Adjust only those controls that are covered by the operating instructions as an improper adjustment of the controls may result in damage and will often require extensive work by a qualified technician to restore the product to its normal operation.
 - If the product has been dropped or damaged in any way.
 - The product exhibits a distinct change in performance.
- **Replacement Parts:** When replacement parts are required, be sure the service technician uses replacement parts specified by Sencore, or parts having the same operating characteristics as the original parts. Unauthorized part substitutions made may result in fire, electric shock or other hazards.

SAFETY PRECAUTIONS

There is always a danger present when using electronic equipment.

Unexpected high voltages can be present at unusual locations in defective equipment and signal distribution systems. Become familiar with the equipment that you are working with and observe the following safety precautions.


- Every precaution has been taken in the design of your MRD 6000 to ensure that it is as safe as possible. However, safe operation depends on you the operator.
- Always be sure your equipment is in good working order. Ensure that all points of connection are secure to the chassis and that protective covers are in place and secured with fasteners.
- Never work alone when working in hazardous conditions. Always have another person close by in case of an accident.
- Always refer to the manual for safe operation. If you have a question about the application or operation call Sencore for assistance.
- **WARNING** – To reduce the risk of fire or electrical shock never allow your equipment to be exposed to water, rain or high moisture environments. If exposed to a liquid, remove power safely (at the breaker) and send your equipment to be serviced by a qualified technician.
- To reduce the risk of shock the MRD 6000 must be connected to a mains socket outlet with a protective earthing connection.
- For the MRD 6000 the mains plug is the main disconnect and should remain readily accessible and operable at all times.
The MRD 6000 is equipped with an internal system battery. The MRD 6000 must be sent to Sencore service for replacement of this battery.
- When installing the MRD 6000 utilizing the DC power supply, the power supply **MUST** be used in conjunction with an over-current protective device rated at 50 V, 5 A, type: Slow-blo, as part of battery-supply circuit.
- To reduce the risk of shock and damage to equipment, it is recommended that the chassis grounding screw located on the rear of the MRD 6000 – be connected to the installation's rack, the vehicle's chassis, the battery's negative terminal, and/or earth ground.

CAUTION – Danger of explosion if battery is incorrectly replaced. Replace only with the same or equivalent type.

FCC Class A Information

The MRD 6000 has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his or her own expense.

Shielded cables must be used with this unit to ensure compliance with the Class A FCC limits.

 Warning: Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Dolby Digital Information

This product has been manufactured under license from Dolby Laboratories.

“Dolby Digital”, “AC-3”, and “Dolby Digital Plus” are licensed trademarks of Dolby Laboratories.


Package Contents

The following is a list of the items that are included along with the MRD 6000:

1. Declaration of Conformity
2. AC Power Cable
3. Quick Start Guide

Note: If any option cables were ordered with the MRD 6000, they will be included in the box as well.


If any of these items were omitted from the packaging of the MRD 6000 please call 1-800-SENCORE to obtain a replacement. Manuals for Sencore products can be downloaded at www.sencore.com



1) Declaration of Conformity



2) AC Power Cable



3) Quick Start Guide

Table of Contents

Section 1 Overview	10
1.1 Product Introduction.....	11
1.2 Front Panel Overview	11
1.3 Rear Panel Overview.....	12
1.4 Cooling.....	12
1.5 Rack Information.....	12
Section 2 Installation	13
2.1 Rack Installation	14
2.2 Power Connection	14
2.3 AC Power Connection	14
2.4 Maintenance	15
2.5 Network Setup via Front Panel	15
Section 3 Operating the Front Panel	17
3.1 MRD 6000 Front Panel Overview	18
Section 4 Operating the Web Interface	20
4.1 MRD 6000 Web Interface Overview	21
4.1.1 Logging into the MRD 6000 Web Interface	21
4.1.2 Hiding Unused Inputs	21
4.1.3 Buttons and Status Indicators	21
4.1.4 Drag and Drop Menus	22
4.2 Main Panel	22
4.2.1 Configuring Active Inputs	23
4.2.2 Configuring ASI Input	25
4.2.3 Configuring MPEG/IP Input	26
4.2.4 Configuring DVB-S/S2/S2X Input	29
4.2.5 Configuring DVB-S/S2 Input	31
4.2.6 Configuring 8VSB/QAM Input	33
4.2.7 Configuring Turbo PSK Input (Currently Not Available)	34
4.2.8 Configuring DVB-T2/C2/ISDB-T Input.....	34
4.2.9 Configuring DVB-CI Descrambling	36
4.2.10 Configuring BISS Descrambling	37
4.2.11 Configuring Service Selection	40
4.2.12 Configuring Video Services	43
4.2.13 Configuring Audio	44
4.2.14 Configuring SDI Ports - SD & HD Interface.....	45
4.2.15 Configuring SDI Ports- UHD –4K Interface	46
4.2.16 Configuring SDI Audio Embedding	48
4.2.17 Configuring Analog Audio Output	49
4.2.18 Configuring Digital Audio Output	49
4.2.19 PID Filter	50
4.2.20 Configuring ASI Output	51
4.2.21 Configuring the MPEG/IP Outputs	52
4.2.22 Configuring the MPEG/IP MPE Outputs.....	54
4.2.23 Viewing PSIP Information	56
4.3 Admin Panel	57
4.3.1 Changing Unit Password	58
4.3.2 Profiles	58
4.3.3 General Settings	59
4.3.4 Unit Network Configuration	59
4.3.5 MPEG/IP Network Configuration	61

4.3.6	Licensing	62
4.3.7	Date/Time	63
4.3.8	Configuring SNMP	64
4.3.9	Syslog	65
4.3.10	In-Band Control	66
4.3.11	Updating the MRD 6000	67
4.3.12	Reboot Unit	68
4.3.13	Reset Defaults	68
4.4	Reporting Panel	69
4.4.1	Active Alarms	69
4.4.2	Event Logs	70
4.4.3	Configuring the Logs	71
4.5	About Panel	73
4.6	System Recovery	73
Section 5 Appendices		74
Appendix A	– Acronyms and Glossary	75
Appendix B	– Error and Event List	78
Appendix C	- Specifications	80
Appendix D	– Pinouts for Analog Audio and Relay Connectors	89
Appendix E	– MRD 6000 Audio Explanation	91
Appendix F	– MRD 6000 Discrete Audio Configuration	94
Appendix G	– Open Source Software	94
Appendix H	– Warranty	96
Appendix I	– Support and Contact Information	96

Section 1 Overview



Introduction

This section includes the following topics:

1.1	Product Introduction.....	11
1.2	Front Panel Overview	11
1.3	Rear Panel Overview.....	12
1.4	Cooling.....	12
1.5	Rack Information.....	12

1.1 Product Introduction

The MRD 6000 4K/UHD receiver decoder continues Sencore's long history of leadership and innovation in professional receiver/decoders. It is built with the latest-generation 4K/UHD ASIC decoder technology delivering reliable, cost-effective monitoring, turn-around, signage, hospitality, and enterprise solutions.

The product boasts a full complement of cutting-edge features, including HEVC decoding up to MP@HT and M10P@HT to L4.1 on streams to 40 Mbps for decoding professional 4K and consumer UHD formats with 4:2:0 chroma 8 and 10 bit. It outputs HDMI 2.0 and 4x3G-SDI of 4K/UHD to 4Kp60 and 2160p60 formats. It includes legacy format decoding of MPEG 2 and H.264 up to HP@L4.2.

The MRD 6000 decodes and outputs 4K/UHD video with dual audio and includes core features required in professional video delivery networks. Every MRD 6000 ships with a full complement of basic inputs and outputs, including ASI input and output, SD/HD/SDI outputs, and an HDMI digital video output. The HDMI output makes monitoring as easy as finding the nearest standard consumer television or PC monitor.

The MRD6000 further features MPEG/IP I/O, DVB-S/S2/S2X satellite inputs, QAM/VSF RF receiver, DVB-T/T2, C/C2, & ISDB-T inputs, BISS descrambling, and dual DVB-CI CAM slot options. Its configurable feature set makes the MRD 6000 the ideal choice for contribution reception or demanding distribution applications which require a future-proof set of specifications.

The receiver maintains Sencore's long tradition of ease of use, with a straight-forward web interface accessible via all major browsers and complete control of the unit via the front panel keypad, and is backed by Sencore's best-in-class staff of ProCare support engineers.

1.2 Front Panel Overview

The MRD 6000 can be controlled from the front panel using the LCD screen and buttons that are shown below. A detailed description of using the front panel can be found in Section 0. All hardware listed below comes standard except for the DVB-CI slots which are a factory installed option.



1. LCD screen: Shows menus for user status and unit control
2. Input Indicator: Light indicates input signal presence (green) or absent (red)
3. Error Indicator: Light indicates red when unit is in alarmed condition
4. Up, Down, Left, Right buttons: Provides navigation/entry within LCD screen menus
5. Back and Enter Buttons: Provides navigation within LCD screen menus

1.3 Rear Panel Overview

The MRD 6000 comes standard with all of the hardware back panel features shown and listed below except where noted as a factory installed option. Option cards are available for the MRD 6000. Examples include a Quad Input DVB-S/S2/S2X card or dual port MPEG/IP Input/Output card. ASI is a standard input and output on all MRD 6000 units. The external genlock reference connection (3) is not currently an option for the MRD 6000 model.



1. RJ45 Management Network Port(s)
2. Relay Output Connector
3. Digital Audio Outputs
4. 15-Pin Analog Audio Connectors (See Appendix D)
5. Composite Video Output (BNC connector)
6. SDI Outputs (Five BNC provide Quad3G/3G/HD/SD-SDI)
7. Digital Video Output Connector (HDMI)
8. ASI Input and ASI Output Connectors
9. Option Card Slot #1 (factory installed)
10. Option Card Slot #2 (factory installed)
11. Chassis ground
12. Unit Venting

1.4 Cooling

The MRD 6000 is cooled via forced induction through the front of the unit and exhausted through the vents in the rear of the chassis. The MRD 6000 is equipped with a temperature controlled status indicator. If the temperature inside the unit exceeds 60°C the red “Error” text will illuminate on the front panel and a description of the error will appear in the “Error List.”

1.5 Rack Information

The MRD 6000 is intended to be mounted in a standard 19” rack. It occupies 1RU of rack space and the connections are all on the rear of the unit.

Section 2 Installation



Introduction


This section includes the following topics:

2.1	Rack Installation	14
2.2	Power Connection	14
2.3	AC Power Connection	14
2.4	AC Dual Redundant Power Connection (optional)	15
2.5	DC Power Connection	15
2.6	Maintenance	15
2.7	Network Setup via Front Panel	15

2.1 Rack Installation

To install the MRD 6000 into a rack use the following steps:

1. Determine the desired position in the rack for the MRD 6000 making sure that the air intake on the front of the unit and the exhausts on the sides of the unit will not be obstructed.
2. Insert the rack mount clips into place over the mounting holes in the rack.
3. Slide the MRD 6000 into position in the rack.
4. Secure the MRD 6000 to the rack by installing the four supplied screws through the front mounting holes and tightening.
5. If needed, secure a grounding wire use the grounding location on the rear panel of the MRD 6000. See Section 1.3 for grounding location.



2.2 Power Connection

Using the proper power connections is vital to the safe operation of the MRD 6000. Only use the supplied 3-prong power connector or one with equal specifications. NEVER tamper with or remove the 3rd – prong grounding pin. This could cause damage to the MRD 6000, personnel, or property.

2.3 AC Power Connection

The MRD 6000 is intended for use on either 120V or 240V systems. The power supply will automatically detect the system it is connected to. To hook up the power use the following steps:

1. Locate the AC power cord that was included with the MRD 6000.
2. Plug the female end of the power cord (end with no prongs) into the back of the unit.
3. Locate a protected outlet (usually inside of the rack) to plug the male end of the power cable into.

2.4 Maintenance








The MRD 6000 is a maintenance-free piece of equipment. There are no user serviceable parts on the inside of the unit

2.5 Network Setup via Front Panel

The MRD 6000 can be setup on a network connection to allow remote management and SNMP configuration. For these features to work, the network settings for the MRD 6000 must first be configured properly for the network it is connected to.

Static IP Address

To setup the MRD 6000 with a static IP address, use the following steps:


1. Press the  button.
2. Use the  and  buttons to move the cursor to “Admin”, then press the  button.
3. Use the  and  buttons to move the cursor to “Unit Networking”, then press the  button.







```

Main Menu      ↕↕↕
Baseband Outputs
Transport Stream Outputs
>Admin
Active Errors
  
```

```

Admin          ↕↕↕
>Unit Networking
System Time
About System
Voltage Levels
  
```




Note: The first menu displayed is status menu. In order to begin making changes to networking settings press the  button.

4. Use the  and  buttons to move the cursor to “DHCP”, then press the  button.
5. Use the  and  buttons to change the selection to “Disabled” then press the  button.

```
















Configure Network  ↕↕↕
Host Name: .....
>DHCP: Disabled
  
```

IP Address/Subnet Mask/Gateway

1. Use the  and  buttons to move the cursor to “IP”, then press the  button.

```

Configure Network  ↕↕↕
Host Name: .....
DHCP: Disabled
>IP: 0.0.0.0
Mask: 0.0.0.0
  
```

2. Use the  and  buttons to select the column to edit and use the  and  buttons to change the IP, then press the  button to save the selection.
3. The cursor will now be on "Mask".
4. Use the  and  buttons to select the column to edit and use the  and  buttons to change the Subnet Mask, then press the  button to save the selection.
5. The cursor will now be on "Gateway".
6. Use the  and  buttons to select the column to edit and use the  and  buttons to change the Gateway, then press the  button to save the selection.

```

Configure Network  ⇐↑⇐
Host Name: .....
DHCP: Disabled
>IP: 000.000.000.000
Mask: 0.0.0.0

```

```

Configure Network  ⇐↑⇐
Host Name: .....
DHCP: Disabled
IP: 0.0.0.0
>Mask: 000.000.000.000

```







```

Configure Network  ⇐↑⇐
DHCP: Disabled
IP: 0.0.0.0
Mask: 0.0.0.0
>Gateway: 000.000.000.000

```

DHCP

The MRD 6000 can be configured to use DHCP to obtain an IP address/Subnet Mask/Gateway.

1. Use the  and  buttons to move the cursor to "DHCP:" then press the  button.
2. Use the  and  buttons to change the selection to "Enabled" then press the  button to save the selection.

```

Configure Network  ⇐↑⇐
Host Name: .....
>DHCP: Enabled

```

Note: It may take up to a minute for the MRD 6000 to obtain an IP address. During this time the unit will display a "busy" message next to DHCP.

Section 3 Operating the Front Panel



Introduction


This section includes the following topics:

3.1	MRD 6000 Front Panel Overview	18
-----	-------------------------------------	----

3.1 MRD 6000 Front Panel Overview




The MRD 6000 front panel allows the user to configure all settings that are present in the web interface using the buttons located on the front of the unit. The screen below is the idle screen of the MRD 6000. This idle screen allows the user to view the incoming bitrate of the active input, which input is set to active, the management IP address of the unit and the service currently set to decode.



1. Bitrate of incoming stream displayed in Mbps.
2. Current active input.
3. IP address of management port.
4. Current decoded service.

The following figure shows a typical screen on the front panel. Several important features have been circled and noted below. These features are common to all screens and assist when navigating, viewing and editing unit information. The **BACK** button allows the user to return to the home screen, cancel settings and go back a menu. In order to edit a selected parameter the **ENTER** button must be pressed. Once a parameter has been changed the **ENTER** button must be pressed again before the change takes effect on the unit.



1. Screen title.
2. Icons indicate which control buttons are currently valid for entry.
3. Cursor shows which line is active.
4. When editing, active character or item is highlighted.

Section 4 Operating the Web Interface



Introduction

This section includes the following topics:

4.1	MRD 6000 Web Interface Overview	21
4.2	Main Panel	22
4.3	Admin Panel	57
4.4	Reporting Panel	69
4.5	About Panel	73

4.1 MRD 6000 Web Interface Overview

4.1.1 Logging into the MRD 6000 Web Interface

To open the MRD 6000 web interface use one of the following supported browsers and navigate to the unit's IP address:



- Internet Explorer 7 & above
- Firefox 3.5 & above
- Google Chrome

The user will need to login to the web interface. By default the admin user account is available without a password. Press the login button in order to login to the web interface.





A login dialog box titled "Login" with a user icon. It contains two input fields: "User:" with a dropdown menu showing "admin" and a "Password:" field. A "Login" button with a key icon is at the bottom right.


4.1.2 Hiding Unused Inputs


The MRD 6000 web interface allows the user to hide inactive inputs using the  button or show all available inputs by click the  button. Only the inputs configured as the Primary Input and Backup Input (see Section 4.2.1) will be displayed when unused inputs are hidden.

4.1.3 Buttons and Status Indicators




When the  icon is shown user configuration is available. Clicking this button will open menus where settings can be changed by the user.



When the  icon is shown additional status information can be viewed. Clicking this button expands the menu to display the additional status information. All text in status


menus shown in **ORANGE** are user configurable settings. Text shown in **BLUE** is not user configurable and is strictly a status or value. To minimize the status windows again click the  icon.

Status in the MRD 6000 web interface is shown with LED status indicators:

Green LED		Status is good. No errors are present and function is operating normally.
Red LED		Status indicates function is affected by active error. To view the errors navigate to Alarms panel to view Active Errors.
Grey LED		Status is inactive. Function is currently disabled or unavailable.

4.1.4 Drag and Drop Menus

Certain menus in the MRD 6000 allow the user to drag and drop items to auto populate fields. Conditional Access and Service Selection menus are some examples of menus that drag and drop can be used. In the example below a service in the transport stream view on the right hand side of the window is selected and dragged over to auto populate the PIDs in the service selection section.



4.2 Main Panel

The Main panel of the MRD 6000 web interface is used to configure the unit to decode, de-encapsulate and demodulate. When configuring the MRD 6000 the user begins at the top of the menu and works down. The inputs are configured, then descrambling (if present), then service or PIDs are selected for decode, then outputs are configured. Pictured below is a fully populated unit with all options licensed.

[Main](#)
[Admin](#)
[Reporting](#)
[About](#)

Main Control Panel

Inputs			
	Input Selection	Active: ASI	Primary: ASI Backup: None
	ASI	Null Stripped: Disabled	0.000 Mbps

Conditional Access	
	BISS Operation Mode: Disabled
	DVB-CI Bottom Slot (None): Disabled Top Slot (None): Disabled

Transport Stream Processing	
	SCTE35
	ESAM

Decoding			
	Service	Service: 2	Mode: Service Lock On Backup: Use Primary Service
	Video	PID: 0 (-- --@-- -- --)	Native Format: 0x0 -- --fps Video Bitrate: 0.000 Mbps
	SCTE35	PID: --, --, --, --	Section Presence: Not Present
	Additional Data		

Baseband Processing			
	Video	Output Format: 1920x1080i 16x9 29.97fps	
	Audio		
	Genlock	External Format: None	Ref. Source: Disabled Color Reference: Not Present
	Ancillary Data		

Baseband Outputs	
	SDI Port 1 & 2
	Composite
	Analog Audio
	Digital Audio

Data Outputs	
<input type="button" value="Show Unused Outputs"/>	
	PID Filter
	ASI Source: Unmodified Input 0.000 Mbps

4.2.1 Configuring Active Inputs

This menu allows the user to configure a primary and backup input. In case there is an input failover the MRD 6000 is capable of detecting the failed state and switching to a secondary backup input in order to provide a continuous output. Which input is primary and backup, how the inputs switchover and restore and switchover timing is all user configurable. The user can force the MRD 6000 to switch between the Primary and Backup Inputs by clicking the **Switch to** button. To change the active input and failover settings click the icon next to Input Selection:

Inputs				
Hide Unused Inputs Switch to Primary Input				
Input Selection	Active: ASI	Primary: DVB-S2 Slot 1 Port A	Backup: ASI	
ASI				
MPEG/IP Slot 2 Stream 1	*:5000	Packet Status: Not Present	FEC: Not Present	
MPEG/IP Slot 2 Stream 2	239.192.0.200:10000	Packet Status: Not Present	FEC: Not Present	
DVB-S2 Slot 1 Port A	4140.0 MHz	Level: -55 dBm	C/N: 16.7 dB	Link Margin:

Active Input Indicator

Configure Inputs

Primary Input:

Backup Input:

Switch On:

Restore On:

Switchover (secs.):


Active Input and Failover Configuration Menu

Setting	Range	Description
Primary Input	ASI	Used for both normal operation and input failover settings. During normal operation this input will be the active input.
	MPEG/IP Slot X Stream X	
	DVB-S2 Slot X Port X	
	DVB-S2X Slot X Stream X	
	8VSB/QAM Slot X	
	DVB-T2/C2/ISDB-T Slot X	
	None	
Backup Input	ASI	During failover operation this input will become the active input. The catalyst for what causes the unit to switch to this input is configured in the following setting.
	MPEG/IP Slot X Stream X	
	DVB-S2 Slot X Port X	
	DVB-S2X Slot X Stream X	
	8VSB/QAM Slot X	
	DVB-T2/C2/ISDB-T Slot X	
	None	
Switch On	Manual Only	<i>Manual Only:</i> the unit will not switch inputs automatically. The user must manually switch inputs.
	TS Sync Loss	

	Decode Failure	<p><i>TS Sync Loss:</i> the MRD 6000 will switch from the primary to the backup input if the primary stream loses synchronization for the duration of the Switchover Interval.</p> <p><i>Decode Failure:</i> the unit will switch to the backup input when it encounters decoding errors on the primary input.</p>
Restore On	Manual Only Primary Input TS Restored Backup Input TS Sync Loss Decode Failure	<p><i>Manual Only:</i> the unit will not restore to the primary input automatically. The user must manually switch inputs.</p> <p><i>Primary Input TS Restored:</i> the MRD 6000 restores to primary when the Primary input regains transport stream synchronization.</p> <p><i>Backup Input TS Sync Loss:</i> the unit will switch from backup to primary when the backup stream loses synchronization for the duration of the Switchover interval.</p> <p><i>Decode Failure:</i> the unit restores to the Primary Input when the Backup Input experiences a decoding error.</p>
Switchover	1-20 seconds	The time in seconds which <i>Switch On</i> or <i>Restore On</i> value must remain in the configured state before the MRD 6000 switches between the Primary Input and Backup Input or vice versa.

4.2.2 Configuring ASI Input

This menu allows the user to either Enable or Disable the ASI Input on the MRD 6000. The ASI ports can be configured as either an input or output. ASI inputs can be configured to enable or disable the null stripped feature. ASI outputs can be configured to pass the selected TS input directly unmodified to the output or apply PID filtering to the output.




Configure ASI Port 2

Direction: Output

Port: Enabled

Source: Unmodified Input

Apply Cancel



Configure ASI Port 1

Direction: Input

Port: Enabled

Null Stripped: Enabled

Apply Cancel

Setting	Range	Description
Direction	Input	Configure the ASI port to either an input or an output. Applies only to main board revision J or later. Main board version can be located on the about tab under the Options section.
	Output	
Port	Enabled	This setting allows the user to enable or disable the ASI Input to the MRD 6000.
	Disabled	
Null Stripped	Disabled	Enabling Null Stripped allows the MRD 6000 to receive streams that do not contain null packets. (i.e. VBR Transport Streams)
	Enabled	

4.2.3 Configuring MPEG/IP Input

If the MPEG/IP Input card was selected as a factory installed option, the following menus and options will be available for configuration. This menu allows the user to configure the MPEG/IP inputs. Each MPEG/IP card has two ports that can be set to receive and/or transmit. This menu is for setting up the reception of MPEG/IP unicast or multicast transport streams. The menu for Stream 1 and 2 have the same settings. IGMPv2 is used to join/leave multicast streams by default if no IGMP Filter addresses are entered. If IGMP Filter Mode addresses are specified then IGMPv3 is used.

General and Advanced options for IP input

Setting	Range	Description
Receive	Enabled Disabled	This setting allows the user to enable or disable these input stream settings.
Physical Connector	Port 1 Port 2	The physical connector on the MPEG/IP card that will be used to receive the input.
Mode	Multicast Unicast	<i>Multicast</i> setting allows the unit to receive multicast streams. Multicast streams originate from the IP range 224.0.0.0 – 239.255.255.255. <i>Unicast</i> allows the unit to receive unicast streams. Unicast streams originate directly from a source device.
Destination IP	224.0.0.0 – 239.255.255.255	This setting is only available when receiving a multicast stream. This address is the IP address the source device is sending to.
Destination Port	0 - 65535	This is the UDP port the source device is sending to. This is the only setting required to receive a unicast stream.
FEC	Enabled	Enabling FEC (Forward Error Correction) tells the MRD 6000 to look at Destination

	Disabled	Port +2 and Destination Port +4 for a SMPTE 2022 FEC Matrix.
Internal Source Filter	Enabled	Enabling Source filtering disables IGMP V3 filtering and allows a user to whitelist a single IP address for a given multicast and block all other source IP's
	Disabled	
Internal Source Filter IP	0.0.0.0 – 255.255.255.255	Source IP for whitelist. All other source IP addresses are blocked
IGMP Filter Mode	Exclude	Used on networks supporting IGMPv3. If this setting is set to <i>Exclude</i> any streams originating from the user defined IP addresses will be rejected. If this setting is set to <i>Include</i> any streams originating from the user defined IP addresses will be received.
	Include	
Null Stripped	Enabled	Enabling Null Stripped allows the MRD 6000 to receive streams that do not contain null packets. (i.e. VBR TS Streams)
	Disabled	
RTP SSRC	Enabled	Enabling RTP SSRC allows the MRD 6000 to filter the input by the user defined value. Only streams containing the user defined value will be received by the MRD 6000.
	Disabled	
SSRC Filter Value	0 - 4294967295	The Filter Value the MRD 6000 checks for before receiving a stream with RTP SSRC.
Buffer Mode	Size (KB)	Allows option to set buffer mode to Size in KB or Delay ms
	Delay (ms)	
Buffer Size (KB)	1 – 4000 KB	This setting determines how much data is received before the MRD 6000 starts decoding. Increasing this value will allow the MRD 6000 is receive streams on networks with high network jitter. Increasing this value also increases the latency of the MRD 6000.
Buffer Delay (ms)	1 – 4000 ms	The buffer delay setting allows the buffer size to be set by delay time. The Buffer delay time will be determined by the input data rate.
Statistics Reset Mode	Manual	Statistics can be viewed by hitting the + symbol next to the MPEG/IP option card on the main window. Selecting Auto will reset the statistics on a chosen interval. When the reset occurs, statistical information for that period will be logged. Selecting Manual will only clear the statistics by hitting the refresh button.
	Auto	
Reset Interval (min)	5-65535	Interval in which the Auto option will reset and log the statistics displayed on the main window

MPEG/IP Slot 2 Stream 1 224.0.211.101:5000 Packet Status: Not Present

Status	Statistics
Buffer Delay: 0 ms	Out of Order Packets: 0
Sync Status: Unlocked	Duplicate Packets: 0
Packets Per Frame: 0	Lost Packets: 0
Encapsulation: UNKNOWN	Corrected Packets: 0
FEC Columns (L): 0	Uncorrected Packets: 0
FEC Rows (D): 0	IAT (ms): 0.000
Corrected Packets / FEC Period: 0	Max IAT (ms): 0.000
	Statistics Reset Mode: Manual
	Reset Interval: 10 min
	Last Reset: 01/01/1970 00:00:00

IP statistics menu

4.2.4 Configuring DVB-S/S2/S2X Input

If the DVB-S/S2/S2X input card was selected as a factory installed option, the following menus and options will be available for configuration. This menu allows the user to configure the DVB-S/S2/S2X inputs. The input card is equipped with dual demodulators and four ports (labeled A, B, C and D). This configuration allows the card to receive two signals simultaneously for fast switching between primary and backup inputs. The menu for both demodulators have the same settings. The input card will automatically detect modulation and symbol rate during signal acquisition. LNB Power configuration for this input card is done in the Admin tab.

Configure DVB-S2X Slot 2 Stream 2

Receive:	Enabled
Physical Connector:	Port D
Satellite Frequency (MHz):	1600
Symbol Rate Mode:	Auto
Symbol Rate (MSps):	20
Manual Search Range:	Enabled
Search Range (MHz):	6
LO Offset (MHz):	0.0
PL Scrambling Code:	0
ISI:	0

Apply Cancel

Setting	Range	Description
Receive	Enabled	This setting allows the user to enable or disable this input stream.
	Disabled	
Physical	Port A	This setting allows the user to select which

Connector	Port B Port C Port D	physical RF connector will be used to receive the stream.
Satellite Frequency	C-Band: 4GHz – 8GHz Ku Band: 11.2Ghz – 14.5Ghz L-Band: 950MHz – 2150MHz Dependent on LO Offset	If LO Offset is set to 0 then L-Band frequency is entered into the Satellite Frequency dialog box. If LO Offset to set to a pre-defined option then enter C-band or Ku-Band frequency.
Symbol Rate Mode	Auto Manual	This setting allows user to select if the satellite tuner automatically searches and determines the received signal symbol rate or if it is entered manually in the space below
Symbol Rate (Mps)	0.5 to 60	If Symbol Rate Mode is set to Manual then enter the satellite receive signal symbol rate
Manual Search Range	Enabled Disabled	This setting determines the satellite receiver automatic fine tuning (AFT) search range. Disabled by default – permits the receiver to auto tune or AFT range (+/- 20 MHz). Enabled allows the user to enter a manual range limiting or expanding the AFT search range
Search Range (MHz)	.5 – 70 MHz	If the Manual Search Range is set to Enabled then enter a MHz value for an AFT search range. The entered value includes a positive and negative search total range. For example: 10 MHz enables a +/- 5 MHz search range.
LO Offset	5150 9750 10600 10750 11250	The offset in MHz that the local oscillator is operating. Set to the LO frequency when you want to enter the Satellite transponder frequency in the Satellite Frequency field. Set to 0.0 when you want to enter the L-Band frequency in the Satellite Frequency field. <i>Note that this setting and the Satellite Frequency setting determine the L-Band frequency input to the receiver.</i>
PL Scrambling Code	0 – 262141	The MRD has the ability to receive satellite signals scrambled using PL Scrambling. In order to receive the stream, enter the value of the incoming signals PL Scrambling code.
ISI	Enter input stream identifier (ISI)	Enter unique ID of the stream you want to receive within the DVB-S2/S2X satellite multi-stream (Advanced MRD 60916 licensed feature)

4.2.5 Configuring DVB-S/S2 Input

If the DVB-S/S2 Input card was selected as a factory installed option, the following menus and options will be available for configuration. This menu allows the user to configure the DVB-S/S2 inputs. Each DVB-S/S2 input card has four ports (labeled A, B, C and D) which only one port can be active at a time. This menu is for setting up the reception of DVB-S/S2 satellite signals. The menu for Port A, B, C and D have the same settings.

Setting	Range	Description
Port	Enabled Disabled	This setting allows the user to enable or disable this reception port.
Mode	DVB-S DVB-S2 Auto	This setting allows the user to choose between <i>DVB-S</i> or <i>DVB-S2</i> modulation schemes. Setting to Auto will have the unit automatically detect whether the input is DVB-S or DVB-S2.
Satellite Frequency	C-Band: 4GHz – 8GHz Ku Band: 11.2Ghz – 14.5Ghz L-Band: 950MHz – 2150MHz Dependent on LO Offset	If LO Offset is set to 0 then L-Band frequency is entered into the Satellite Frequency dialog box. If LO Offset to set to a pre-defined option then enter C-band or Ku-Band frequency.

Wide Search	Enable Disable	When Enabled the search range may be extended depending on the symbol rate. See appendix C for more information.
LO Offset	5150 9750 10600 10750 11250	The offset in MHz that the local oscillator is operating.
Symbol Rate Mode	Manual Auto	The Manual option allows the user to choose the symbol rate. The Auto option automatically detects the incoming symbol rate. Note: Acquisition time may be longer in auto mode, especially when the symbol rate is below 1MSps or above 55MSps.
Symbol Rate	0 - 60	The symbol rate of incoming satellite signal in MSps. Accurate to one decimal place (kSps). Used when Symbol Rate Mode is set to Manual.
PLS Code	0 – 262141	The MRD 6000 has the ability to receive satellite signals scrambled using PL Scrambling. In order to receive the stream, enter the value of the incoming signals PL Scrambling code.
LNB Power	Off 13 VDC 14 VDC 18 VDC 19 VDC	The MRD 6000 has the ability to provide the necessary voltage to power an LNB. Select the correct voltage to supply to the LNB.
22kHz Tone	Enabled Disabled	Enabling or disabling the 22khz tone allows the MRD 6000 to trigger the LNB to switch polarities.
Multistream State	Enabled Disabled	The MRD 6000 has the ability to receive multistream satellite signals. If the signal is multistream capable, enable this setting. This option is only available in DVB-S2 Mode. <i>NOTE: This is a licensed feature.</i>
ISI	0-255	This setting is the ISI (Input Stream Identifier) the MRD 6000 uses to filter multistream input. This option is only available if Multistream is licensed and enabled.

4.2.6 Configuring 8VSB/QAM Input

If the 8VSB/QAM Input card was selected as a factory installed option, the following menus and options will be available for configuration. This menu allows the user to configure the 8VSB/QAM input. This menu is for setting up the reception of 8VSB off air signals or QAM cable signals.

Setting	Range	Description
Receive	Enabled Disabled	This setting allows the user to enable or disable this reception port.
Mode	8VSB 64-QAMB 256-QAMB	This setting allows the user to choose between 8VSB or QAM modulation schemes.
Channel Plan	Off Air FCC Cable HRC Cable IRC Cable	If 8 VSB is the selected Mode, the only available option is <i>Off Air</i> . If either 64-QAMB or 256-QAMB is the selected Mode, this setting allows the user to choose which Cable scheme is used.
Channel	Off Air: 2-69 FCC, HRC, or IRC Cable: 2-158	This setting is for the desired channel to be received.
Low RF Level (dBmV)	-34 - +40	This is the Low RF Level threshold when the <i>Low Level</i> Alarm will be triggered in dBmV
Low MER (dB)	0 – 40	This is the Low MER threshold when the <i>Low MER</i> Alarm will be triggered in dB.

4.2.7 Configuring Turbo PSK Input (Currently Not Available)

Reception of a Turbo PSK satellite signal requires a special input receiver card option which is not currently available for the MRD 6000. Please contact Sencore for an alternative model receiver/decoder for this application.

4.2.8 Configuring DVB-T2/C2/ISDB-T Input

If the DVB-T2/C2/ISDB-T Input card was selected as a factory installed option, the following menus and options will be available for configuration. This menu allows the user to configure a DVB-T/T2/C/C2 or ISDB-T input.

Configure DVB-T2/C2/ISDB-T Slot 2

General

Receive: Enabled

Mode: DVB-T

Channel Plan: Eur-Asia-Afr

Channel: 21

Advanced

Frequency (MHz): 474

Bandwidth: 8 MHz

PLP ID: 0

Profile: Auto

Low RF Level (dBmV): -10

Low MER (dB): 20

Apply Cancel



Setting	Range	Description
Receive	Enabled Disabled	This setting allows the user to enable or disable this reception port.
Mode	DVB-T DVB-T2 DVB-C DVB-C2 ISDB-T	This setting allows the user to choose between <i>DVB-T/T2/C/C2</i> or <i>ISDB-T</i> modulation schemes.
Channel Plan	Australia Eur-Asia-Afr	This setting allows the user to select which channel plan they would like to use. Channel Plan options are tied to which modulation

	Ireland New Zealand Taiwan South Africa South America United Kingdom European Cable Japan Philippines	mode is selected.
Channel		Select a channel from the channels available in the dropdown. The list of available channels will be based on which channel plan is selected
Frequency (MHz)	42-1002	Selecting a channel from the channel dropdown will populate this field automatically based on the user selected channel. A user can manually select a frequency if desired
Bandwidth	1.7 MHz 5 MHz 6 MHz 7 MHz 8 MHz	Selecting a channel from the channel dropdown will populate this field automatically based on the user selected channel plan. A user can manually select channel bandwidth if desired.
PLP ID		Unique PLP ID used to select a particular stream within the DVB-T2 or DVB-C2 input signal
Profile	Auto Base Lite	Select the DVB-T2 profile to use
Low RF Level (dBmV)	-34 - +40	This is the Low RF Level threshold when the <i>Low Level</i> Alarm will be triggered in dBmV
Low MER (dB)	0 - 40	This is the Low MER threshold when the <i>Low MER</i> Alarm will be triggered in dB.

4.2.9 Configuring DVB-CI Descrambling

This section will describe how to configure DVB-CI descrambling in the MRD 6000. First, the user will need to configure the CAM slots and descrambling mode. Once this is complete the user can configure which services or PIDs to descramble.






4.2.9.1 Configuring DVB-CI Slots


This menu allows the user configure the DVB-CI slots in the MRD 6000. The MRD 6000 has two DVB-CI slots, a top and bottom, where CAM Modules can be inserted. Both slots are individually configurable using the Bottom Slot and Top Slot tabs. CAM Modules can be reset manually using the  Reset button. The  MMI button opens the MMI (Man Machine Interface) for the CAM in the respective slot. MMI support is dependent on what is supported by the CAM



Setting	Range	Description
Mode	Descramble Decoded PIDs Descramble Selected PIDs Descramble Selected Services	<i>Decoded PIDs</i> sets the MRD to descramble only the PIDs of the service that is currently set to decode. If the PIDs change in the incoming stream the MRD will adapt to these changes, provided that Service Selection is set to "Service Lock" (Refer to Section 4.2.11). <i>Selected PIDs</i> sets the MRD to descramble PIDs set in the Descramble Services window (Refer to Section 4.2.9.2). If the PIDs change in the incoming stream the MRD will not adapt to these changes and will not be able to descramble. <i>Selected Services</i> sets the MRD to descramble Services set in the Descramble Services window Refer to Section 4.2.9.2). If the Services change in the incoming stream the MRD will not be able to descramble.
Top Slot	Enabled	This setting allows the user to enable or disable the DVB-CI slot.
Bottom Slot	Disabled	

4.2.9.2 Configuring Service Descrambling

This menu allows the user to select the services the MRD 6000 will descramble using the CAM Modules and Smart Cards inserted into the DVB-CI slots. See Section 4.2.9.1 to configure these slots. These options are applicable only if the Mode in the DVB-CI settings is set to Selected PIDs or Selected Services (Refer to Section 4.2.9.1). The drag and drop method can be used to drag services from the right column to the left column. The drop down menu next to each selected service allows the user to choose either the bottom or top slot to descramble the service. If in Selected PIDs mode, PIDs to descramble can be added manually by clicking  Add PID button. If in Selected Services mode, Services to descramble can be added manually by clicking the  Add Service button. The icons next to each service indicate whether the service is scrambled or not scrambled. Scrambled services will show the  icon next to them while services that are not scrambled will show the  icon. Clicking the  Refresh button forces the MRD 6000 to rescan the transport stream for changes.



DVB-CI Service Descrambling Menu


4.2.10 Configuring BISS Descrambling


This section will describe how to configure BISS descrambling in the MRD 6000. There are two types of BISS descrambling.

In “Descramble All PIDs” or “Descramble Decoded PIDs” mode, the user simply configures a BISS key set and selects it from the drop down.

For streams with multiple, per-service keys the user must first configure the key sets, and then assign them to services.

4.2.10.1 Configuring BISS Keys

This menu allows the user to configure BISS descrambling. 12 unique BISS keys can be entered. If the BISS mode is set to Mode E a  icon will appear next to Mode E Injected ID. This icon allows the user to unlock and modify the Injected ID.






BISS Menu

Setting	Range	Description
Operation Mode	Disabled	Descramble Decoded PID's will descramble the pids that are currently assigned to be decoded by the MRD 6000.
	Descramble Decoded PIDs	
	Descramble Selected Services	Descramble Selected Services will allow the user to select service(s) to be descrambled on the Selected Services tab.
	Descramble All PIDs	Descramble All PIDs will apply the selected key to the entire transport stream.
Selected Key	Key 1-12	Select a key to configure.
Alias	16 characters	Set an Alias for the selected key.
Mode	Mode 1	This setting sets the Mode of the BISS key that has scrambled the transport stream.

Mode E		
Mode 1 Session Word	N/A	If Mode 1 is selected the user enters the BISS session word here.
Mode E Session Word	N/A	If Mode E is selected the user enters the BISS session word here.
Mode E Injected ID	N/A	If Mode E is selected the user enters the BISS injected ID here.

4.2.10.2 Configuring Per-Service Descrambling

This menu allows the user to select the services the MRD 6000 will descramble using the BISS keys configured in Section 4.2.10.1. These options are applicable only if Operation Mode in the BISS settings is set to Descramble Selected Services (Refer to Section 4.2.10.1). The drag and drop method can be used to drag services from the right column to the left column. The BISS key to descramble services can be selected using the drop down menu next to each service. Services can be added manually by clicking  Add Service button. Clicking the  Refresh button forces the MRD 6000 to rescan the transport stream for changes.



BISS Service Descrambling Menu

4.2.11 Configuring Service Selection

This menu allows the user to configure the PIDs or Service the MRD 6000 decodes. Depending on the Selection Mode that is selected, the menu changes to reflect the applicable settings.

Service Lock

In Service Lock mode the MRD is set to decode a specified service number or service name. If the PIDs within the service change at any time, the MRD continues to decode the service. The drag and drop method can be used to populate the Service Name or Service Number dialog boxes.

Service Lock Selection Menu

Setting	Range	Description
Selection Mode	Service Lock	Setting to <i>Service Lock</i> sets the unit to decode any PIDs associated with a service number or service name. Setting to <i>PID Lock</i> sets the unit to decode only the PIDs specified in the PID Lock Configuration matrix. <i>Auto Seek</i> mode will tune the unit to the first service listed in the PAT if a transport stream is present.
	PID Lock	
	Auto Seek	
On Backup	Use Primary Service	Sets the service the MRD 6000 will tune to in case of an input failover. If <i>Use Primary Service</i> is selected the MRD 6000 will tune to the service name specified in the Primary section. If <i>Use Backup Service</i> is selected the service name specified in the Backup section will be tuned. How the MRD 6000
	Use Backup Service	

fails over inputs is configured in Section 4.2.1

Lock Mode	Service Name	If set to <i>Service Name</i> the MRD will decode only services matching the name specified (SDT in DVB or TVCT in ATSC tables must be present in this mode). If set to <i>Service Number</i> the MRD will decode only services matching the number specified.
	Service Number	

Note: S302M Audio Type is auto detected by the MRD 6000

PID Lock Mode


In PID Lock mode the MRD decodes only the PIDs specified by the user in the PID Lock Configuration matrix. The drag and drop method can be used to auto-populate the cells in the matrix. Stream types can be manually defined under the Primary Type and Backup Type columns. Individual cells under Primary and Backup columns can be selected and PIDs can be typed in manually.

PID Lock Selection Menu

Setting	Range	Description
On Backup	Use Primary PIDs	Sets the PIDs the MRD 6000 will tune to in case of an input failover. If <i>Use Primary PIDs</i> is selected the MRD 6000 will tune to the PIDs specified in the Primary PID column. If <i>Use Backup PIDs</i> is selected the service name specified in the Backup PID column will be tuned. How the MRD 6000 fails over inputs is configured in Section 4.2.1.
	Use Backup PIDs	

Auto Seek Mode


In Auto Seek mode the MRD decodes the first service listed in the PAT. All PIDs in this service are automatically selected for decoding. No other configurations are available in this mode. This mode is recommended to verify the MRD is receiving a valid signal and is able to decode. This mode is not recommended for a professional environment as changes in the PAT's listings and order of listings can unexpectedly cause changes the service being decoded.



Auto Seek Menu

4.2.12 Configuring Video Services


The menu allows the user to configure the SDI, Digital Video (HDMI), and Composite output formats of the MRD 6000. Please note that the composite video output is only active if the output video format is SD (720x480i, 720x576i). For all other selected formats, there is no output from the composite video BNC jack. The video format selected determines which of the SDI output jacks is actively outputting.



Setting	Range	Description
Format Mode	Auto Manual	Setting to <i>Auto</i> the MRD 6000 will output video to match the incoming native video format. Setting to <i>Manual</i> the user can define the video format the MRD 6000 will output.
Manual Format	Refer to Appendix C for supported formats.	This setting is the video format the MRD 6000 will output.

4.2.13 Configuring Audio



This menu allows the user to configure the audio downmix settings of the decoder. Two audio presets are available: Transmission and Monitor. These presets can be applied by clicking the **Presets** button. The menus for Audio 1 through Audio 4 all contain the same settings. Note: The number of audio services decoded by the MRD 6000 and listed may vary with licensing.



Setting	Range	Description
Operational Mode	Line Mode	Refer to Appendix E for explanation.
	RF Mode	
	Custom 1	
	Custom 0	
Processing Mode	Downmix	Refer to Appendix E for explanation.
	Discrete	Refer to Appendix F for explanation
Dynamic Range	Enabled	Refer to Appendix E for explanation.
	Disabled	
Downmix	Lo/Ro (Stereo)	When the audio is downmixed in the MRD 6000 two audio channels are created. The channels can be configured using the settings available in the drop down menu. (Refer to Appendix E)
	Lt/Rt (Dolby Surround)	
	Lt/Rt (Auto)	
	Dual Mono	
	Dual Left	
	Dual Right	
Format Mode	Consumer	This option selects the PCM or Dolby Digital format mode. (Refer to Appendix E)
	Professional	

4.2.14 Configuring SDI Ports - SD & HD Interface

The following menus allow the user to configure the SDI video output from ports 1A & 1B when either an SD or HD, non UHD/4K format, is selected for output. See section 4.2.12 for information on output format selection. For SD-SDI or HD-SDI formats a single link connection is used as per SMPTE 259 or SMPTE 292.



SD or HD

Setting	Range	Description
Video Loss Mode	Disable SDI Display Raster	Setting to <i>Disable SDI</i> squelches the SDI output of the MRD in case of an error state. Setting to <i>Display Raster</i> the MRD will display the raster color selected in Section 4.2.12. This Feature is not yet available.

When outputting common SD-SDI or HD-SDI formats port 1A provides the main output. Port 1B provides a second simultaneous output identical to the Port 1A output.




Port 1A: Main Output for all SD and HD-SDI formats

Port 1B: Provides Secondary or Simultaneous Output mirroring port 1A's output

4.2.15 Configuring SDI Ports- UHD –4K Interface

The UHD selection tab provides a menu which provides configuration of the UHD/4K outputs. The Video Loss Mode sets the output to either be disabled (no output) or to output a black raster when an error condition exists which prevents a normal decoded output. The Output Mapping selection configures the quad 3G SDI outputs to carry a 4K format to a compatible quad SDI 3G input device/monitor.



UHD

Setting	Range	Description
Video Loss Mode	Disable SDI Display Raster	Setting to <i>Disable SDI</i> squelches the SDI output of the MRD in case of an error state. Setting to <i>Display Raster</i> the MRD will display the raster color selected in Section 4.2.12. This Feature is not yet available.
UHD/SDI Output Mapping	Two Sample Interleave Square Division	Setting to <i>Two Sample Interleave</i> configures the SDI output for quad 3G SDI format in which each of 4 stream outputs carries ¼ pixels and the picture resolution. Setting to <i>Square Division</i> configures a quad SG SDI output format in which each of 4 streams carries a quarter section of the picture in full resolution. Quad 3G SDI Formats conform to SMPTE 425-3 and SMPTE 425-5

Quad 3G- SDI requires 4 SDI output port/connections. Ports 1A, 2, 3, and 4 on the MRD 6000 provide the respectable outputs for the 4K formats when selected. See section 4.2.12 on configuring the SDI output format.




SDI Link connections 1A,2,3,4 from the MRD 6000 must appropriately match the quad SDI inputs of the receive/monitor device so the 4K image can be properly processed/rendered. The following section provides a brief explanation of the two methods commonly used to interface a 4K SDI signal over four 3G-SDI link connections.

Two Sample Interleave

SMPTE 425-3 and SMPTE 425-5 define new image mapping structures which provide a means to interface 4K over an SDI interface. Interfacing 4K SDI up to 60 fps requires using four 3G-SDI links. Two methods of carrying 4K via 4 link connections include


1. Two Sample Interleave
2. Four Quadrant Division (Square Division).

In each of these methods $\frac{1}{4}$ of the picture image is carried by each of the four link connections. A brief explanation of each follows.



Two Sample Interleave breaks the image into interleaved samples of the entire picture. A line interleaving system has one line with alternating pixels 1 and 2, while the next line has alternating pixels 3 and 4 as illustrated. 3G-SDI link 1 carries the #1 pixels, while link 2 carries the #2 pixels, link 3 the #3 pixels and link 4 the #4 pixels. In this manner each of the 3G-SDI links carries pixels in $\frac{1}{2}$ the scan lines and $\frac{1}{2}$ the pixels in each line of the (1080p resolution) image or frame.

Square Division or Four Quadrants Division



The Square Division method, also referenced as Four Quadrant Division, divides the picture equally in quarter sections as illustrated. Each section is $\frac{1}{4}$ of the 4K image or 1080p. SDI link 1 carries the upper left image pixels, link 2 carries the upper right pixels, link 3 carries the lower left pixels, and link 4 carries the lower right pixels. The SDI receive device assembles the pixels from the 4 links to recreate the image.

Simultaneous HD-SDI output in 4K Mode

The MRD 6000 provides a simultaneous HD-SDI output when you have selected and are outputting a UHD/4K format using Two Sample Interleave. For any of the available UHD/4K formats, SDI output ports labeled 1A, 2, 3, and 4 are used to provide the

UHD/4K SDI output via four 3G-SDI link connections. When outputting the Two Sample Interleave mode 4K SDI, port 1A contains $\frac{1}{4}$ of the image pixels. Port 1B is internally configured by the MRD 6000 to always output a mirror image of the signal on port 1A. Therefore, for all UHD/4K formatted signals with Two Sample Interleave, the Port 1B output is an HD 1080 formatted signal at the 4K frame rate selected. For example, if the MRD 6000 is decoding/outputting a 3180x2160p50 stream, SDI port 1B is outputting a 1080p50 HD-SDI signal.

4.2.16 Configuring SDI Audio Embedding

This menu allows the user to configure SDI embedded audio settings. The MRD 6000 comes standard with the ability to decode two audio services. With additional licensing the MRD 6000 can handle up to four unique audio services. When licensed for four audio services, the user will have four audio pairs available to embed audio in the SDI. These two SDI groups provide inclusion of four audio pairs, with two pairs to each group. All audio pairs share the same options.

The screenshot shows a window titled "Configure SDI Ports" with four tabs: SD, HD, UHD, and Audio. The Audio tab is selected. Inside, there are two sections: "Group 1" and "Group 2". Each section contains two dropdown menus labeled "Pair 1:" and "Pair 2:". In Group 1, Pair 1 is set to "Audio 1 PCM" and Pair 2 is set to "Off". In Group 2, both Pair 1 and Pair 2 are set to "Off". At the bottom right of the window are "Apply" and "Cancel" buttons.

SDI Embedded Audio Configuration Menu

Setting	Range	Description
Group 1-4	Off	Assigning a <i>PCM</i> audio to a Group Pair will embed the decoded or downmixed two channel audio using the settings defined in Section 4.2.13. Assigning <i>Pass-Through</i> to a Group Pair will embed unprocessed compressed audio in the SDI VANC. Selecting Off disables the Group Pair completely.
Pair 1-2	Audio 1-4 PCM Audio 1-4 Pass-through	

4.2.17 Configuring Analog Audio Output


This menu allows the user to configure the analog output outputs of the MRD 6000. Two analog audio outputs are available. The dBu level of the outputs can be adjusted for each of the four audio outputs. For the Analog Output connector pin out refer to Appendix D.

The screenshot shows a window titled "Configure Analog Audio Output". Inside, there are two rows of controls. The first row is for "Analog Output 1", with a dropdown menu currently showing "Off" and a text box for "Level (dBu)" containing the number "4". The second row is for "Analog Output 2", also with a dropdown menu showing "Off" and a "Level (dBu)" text box containing "4". At the bottom right of the window are two buttons: "Apply" and "Cancel".

Setting	Range	Description
Analog Output 1-2	Off Audio 1-2	Assign <i>Audio 1-2</i> to an analog audio output for output. Select <i>Off</i> to disable the analog output completely.
Level	-10 to 4	Level of the analog audio output in dBu.

4.2.18 Configuring Digital Audio Output

This menu allows the user to configure the digital audio outputs of the MRD 6000. The number of outputs available directly correlates with the number of audio services the unit is licensed to support. Up to four digital audio outputs are available .



Setting	Range	Description
Digital Output 1-8	Off	Assigning a <i>PCM</i> audio to a digital output will output the decoded or downmixed two channel audio using the settings defined in Section 0. Assigning <i>Pass-Through</i> to a digital output will output unprocessed compressed audio. Selecting <i>Off</i> disables the digital output completely.
	Audio 1-4 PCM	
	Audio 1-4 Pass-through	


4.2.19 PID Filter

If the PID/Service Filter license is enabled, the following menus and options will be available for configuration. PID filtering will allow the user to create a new output TS by selecting and dragging one or more services/PIDs from the incoming transport stream into the Selected Services/Pids box or use the currently decoded stream. The user can also configure a TS bitrate for each PID filtered stream and select different table inclusion options.

Setting	Range	Description
Select PID Filter	PID filter 1-10	Select which PID filter to configure
TS Bitrate (Mbps)	.25 to 160	Configure the TS Bitrate for the PID filter stream selected
Table Processing Mode	PSI (MPEG)	Adjusted tables: PAT, PMT Passed tables: CAT, NIT Discarded tables: all remaining
Table Processing Mode	SI (DVB)	Adjusted tables: PAT, PMT, SDT Passed tables: CAT, NIT, EIT, RST, TDT, TOT Discarded tables: TSDT, BAT
Selection Mode	Use Selected Services/PIDs Use Decoded Service	Use Selected Services/PIDs will allow the user to select which services are in the new TS. Use Decoded Service will only include the service that is currently selected for decoding by the MRD 6000

4.2.20 Configuring ASI Output

This menu allows the user to configure the ASI output of the MRD 6000. When enabled this output acts as an active loop output of the active input. For example, if the DVB-S/S2 input card is the current active input the ASI output port will output a demodulated signal of the satellite input.



Setting	Range	Description
Port	Enabled	Enable or disable the ASI output port.
	Disabled	
Source	Unmodified Input	Unmodified Input will pass the incoming TS to the output without applying any BISS or DVB-CI decryption
	Descrambled	
	Descrambled and Processed	Descrambled (or Descrambled and Processed) will output the TS with any applied BISS or DVB-CI decryption.
	Pid Filter 1-10	
		PID Filter will output the TS from the PID filter menu option.

4.2.21 Configuring the MPEG/IP Outputs

This menu allows the user to configure the MPEG/IP outputs. Each MPEG/IP card has two ports that can be set to receive and/or transmit. This menu is for setting up the transmission of MPEG/IP unicast or multicast transport streams. The menu for Stream 1 and 2 have the same settings. The menu for Streams 3 through 10 will contain the same options as Transmit 1 and Transmit 2 with one exception: Forward Error Correction is only available (if licensed) on Transmit 1 and 2.

Configure MPEG/IP Slot 2 Stream 1

General Settings

Transmit:

Source:

Physical Connector:

Destination IP:

Destination Port:

Source Port:

TS Packets Per IP Packet:

Differentiated Services:

Encapsulation:

Advanced Settings

FEC:

FEC Columns:

FEC Rows:

Setting	Range	Description
Transmit	Enabled Disabled	Enable or disable the MPEG/IP transmit group.
Source	Unmodified Input Descrambled Descrambled and Processed Pid Filter 1-10	Unmodified Input will pass the incoming TS to the output without applying any BISS or DVB-CI decryption. Descrambled (or Descrambled and Processed) will output the TS with any applied BISS or DVB-CI decryption. PID Filter will output the TS from the PID filter menu option.
Physical Connector	Port 1 Port 2	The physical connector on the MPEG/IP card that will be used to transmit the output.
Destination IP	Multicast - 224.0.0.0 - 239.255.255.255	When sending to a unicast address the destination IP address must match the receiving device's IP address. When sending a multicast the address must be sent within the multicast IP range.
Destination Port	0 - 65535	When sending to a unicast address, the destination port must match the receiving device's port. When sending a multicast, any port within the accepted

		range can be used, but it is good practice to always choose a port >1030 and an even number
Source Port	0 - 65535	This is the port used by the MRD 6000 to transmit the MPEG/IP stream.
TS Packets Per IP Packet	1-7	The number of TS packets that are contained with a single IP packet. Default is 7. Lowering this value below default increases network overhead.
Differentiated Services	Default Assured Forwarding 1-1 to 4-3 Expedited Forwarding	Define the quality of service (QoS) classification the packets carry when transmitted.
Encapsulation	UDP RTP	Sets the Encapsulation to UDP or RTP.
FEC	Off Columns Columns/Rows	Sets the FEC Type or disables FEC.
FEC Columns	1-20 (Columns) 4-20 (Columns/Rows)	Defines the number of Columns used to construct the FEC Matrix. (Columns * Rows must be ≤ 100.)
FEC Rows	4-20	Defines the number of Rows used to construct the FEC Matrix. (Columns * Rows must be ≤ 100.)


4.2.22 Configuring the MPEG/IP MPE Outputs

This menu allows the user to configure the MPEG/IP Multi-Protocol Encapsulation (MPE) outputs. Each MPE Output allows the user to select an MPE data PID from the transport stream to be output.

Setting	Range	Description
Transmit	Enabled Disabled	Enable or disable transmission of de-encapsulated MPE data.
Physical Connector	Port 1 Port 2	The physical connector on the MPEG/IP card that will be used to transmit the MPE data.
PID		Selected MPE PID from the transport stream to use for MPE output
MAC Filter State	Enabled Disabled	Enable or Disable the filtering of output data based on a MAC address in the selected MPE PID
MAC Address	00:00:00:00:00:00 FF:FF:FF:FF:FF:FF	Filtered MAC address that will be transmitted in the MPE output. All data with other MAC addresses in the selected MPE PID will be discarded

4.2.23 Viewing PSIP Information

To view the PSIP information for the applied TS, select the View PSI Tables button located on the right hand side of the Inputs section. This will open a new window that displays all of the PSIP information for the applied TS. The tables displayed will include PAT, PMT and CAT and tables associated with the stream type (DVB,ATSC). SDT tables will be displayed for DVB streams and MGT,TVCT,EIT, ETT, STT tables will be displayed for ATSC streams.



Clicking the Refresh button in the upper left corner will update the tables displayed.

4.3 Admin Panel

Admin Control Panel

Change Password Profiles SNMP MIBs Diagnostics Update Unit Reboot Reset to Defaults Enable UID

General Settings

Configure General Settings

Unit Alias: (No Alias)
Protect BISS-E Injected ID: No

Unit Network Configuration

Mode	IP Address	Subnet Mask	Gateway	Hostname	MAC
Static	10.0.105.100	255.255.0.0	10.0.1.3	(none)	00:06:4D:01:84:EB

MPEG/IP Network Configuration

Configure Card Slot 2: Default Gateway: Port 1 ICMP Response: Enabled

MPEG/IP	IP Address	Subnet Mask	Gateway	MAC	Link Status	Tx Rate (Mbps)	Rx Rate (Mbps)	IGMP
Slot 2 - 1	192.168.1.125	255.255.0.0	192.168.0.1	00:06:4D:01:84:7F	N/A (Down)	0.000	0.000	V3
Slot 2 - 2	192.168.1.126	255.255.0.0	192.168.0.1	00:06:4D:01:84:80	N/A (Down)	0.000	0.000	V3

License Information

Apply License Key

Option	Supported	State	Instances
MRD 58701 - Genlock	Yes	Licensed	1
MRD 58710 - HD 4:2:0, SD 4:2:2/4:2:0 Decoding	Yes	Licensed	1
MRD 58720 - HD/SD 4:2:2/4:2:0 Decoding	Yes	Licensed	1
MRD 58740 - 3G-SDI/1080p60 Video Output	Yes	Licensed	1
MRD 58880 - 4x->8x Audio Service Decoding Upgrade	Yes	Licensed	1
MRD 58916 - DVB-S2 Advanced Feature	Yes	Licensed	1
MRD 58921 - BISS Descrambling	Yes	Licensed	1
MRD 58925 - IP FEC Output	Yes	Licensed	1
MRD 58991 - Multi-service Descrambling	Yes	Licensed	1
MRD 58992 - SCTE 35-104 Conversion License	Yes	Licensed	1

Date / Time

Configure Date / Time

Update Mode: NTP
Current Date: 11/21/2013
Current Time: 13:57:49
NTP Server: 10.0.1.23

SNMP Communities

Configure SNMP Communities

Read-Only Community: public
Read-Write Community: private


SNMP Trap Managers

Configure SNMP Managers

SNMP Managers

To access the Admin Control Panel, click on the **Admin** tab. This menu allows the user to control many aspects of the MRD 6000.

4.3.1 Changing Unit Password


The MRD 6000 can be assigned an access password and the current access password can be changed. In order to make changes to passwords, click the  button. A window will appear to enter the current password and new password.






The 'Change Password' dialog box has a title bar with a key icon and the text 'Change Password'. It contains two text input fields: 'New Password:' and 'Confirm Password:'. At the bottom, there are two buttons: 'Apply' and 'Cancel'.




4.3.2 Profiles

The MRD 6000 has the ability to save all configured settings to multiple profiles. Profiles can be saved locally, renamed and saved to external storage to be used on other MRD 6000s. Profiles can be used to quickly and easily change the configuration of an MRD 6000 to suit different inputs and decoding requirements.





The 'Profile Manager' window has a title bar with a folder icon and the text 'Profile Manager'. Below the title bar are two buttons: '+ Add' and 'Upload'. Below these is a table with the following columns: 'Profile Name', 'Download', 'Rename', and 'Delete'. The table contains 8 rows, numbered 1 through 8. Each row has a green download arrow, a yellow pencil icon, and a red 'X' icon. At the bottom of the window are two buttons: 'Apply' and 'Close'.

Action	Button	Description
Add New Profile		Adds a new profile from current settings. User must name profile before creation is complete.
Upload Profile		Allows the user to browse to external storage or workstation to upload profile to MRD 6000.
Apply Profile		Select a profile from the drop down menu and click this button. The MRD 6000 will apply all settings contained in the profile selected.

Rename Profile		Select a profile from the drop down menu and click this button. The user will be prompted for a new name for the profile.
Delete Profile		Select a profile from the drop down menu and click this button. The user will be prompted to confirm deletion of the profile.
Download Profile		Select a profile from the drop down menu and click this button. The user will be prompted to select a directory to download the profile.

4.3.3 General Settings

The MRD 6000 can be assigned an alias which is displayed in the upper right hand corner of the web interface. The alias can help define which MRD 6000 the operator is currently logged into. The BISS-E Injected ID for BISS Mode E can also be protected from being accidentally changed. Setting the Protect BISS-E Injected ID to Yes will force the user to unlock the dialog box in the BISS Descrambling configuration menu before allowing any changes to be made. The edit the Unit Alias or protect the BISS-E Injected ID click on the  **Configure General Settings** button. The PID Display mode changes how PID values are displayed in the web interface. The values can either be displayed in decimal or HEX values. The ASI Out/Video Sync Function is for special applications purposes. This should remain set to ASI Out.




The image shows a 'General Settings' dialog box with the following fields and options:


- Unit Alias:** A text input field.
- Protect BISS-E Injected ID:** A dropdown menu with 'Yes' selected.
- PID Display Mode:** A dropdown menu with 'Decimal' selected.
- ASI Out/Video Sync Function:** A dropdown menu with 'ASI Out' selected.

At the bottom of the dialog are 'Apply' and 'Cancel' buttons.



4.3.4 Unit Network Configuration

The management port of the MRD 6000 can be configured from the web interface. To make changes to the management port click, the  button under the Unit Network Configuration section. Domain name servers can be configured on the MRD clicking the



button. IP address and web address entries are accepted as Nameserver addresses.

The 'Configure Nameservers' dialog box contains two text input fields. The 'Primary Nameserver' field is set to '172.16.0.86' and the 'Secondary Nameserver' field is also set to '172.16.0.86'. At the bottom right, there are 'Apply' and 'Cancel' buttons.


If the MRD 6000 contains a 58127 option card the unit can be configured to have an optional 2nd control port.

NOTE: Exercise extreme caution when performing changes to this menu as network communication can be lost with the MRD 6000.


The 'Configure TCP Settings' dialog box has a 'Mode' dropdown menu set to 'Static'. Below it is a 'Hostname' text field containing '(none)'. A section titled 'Static Settings' contains three text fields: 'IP' set to '10.0.15.36', 'Subnet Mask' set to '255.255.0.0', and 'Gateway' set to '10.0.1.3'. 'Apply' and 'Cancel' buttons are at the bottom right.

Setting	Range	Description
Mode	DHCP Static	Setting to <i>DHCP</i> will allow the network assign an IP address automatically to the MRD 6000 (if supported). Setting to <i>Static</i> allows the user to manually define all TCP/IP settings for the management port.
Hostname	Valid characters: A through Z 0 through 9 - (hyphen)	This setting allows the user to define an optional unit Hostname.
IP	Four decimal octets: XXX.XXX.XXX.XXX	This option is only available if Static Mode is set. This is the IP address assigned to the management port.

Subnet Mask	255.0.0.0 – 255.255.255.254	This option is only available if Static Mode is set. This is the Subnet Mask assigned to the management port.
Gateway	Four decimal octets: XXX.XXX.XXX.XXX	This option is only available if Static Mode is set. This is the Gateway address assigned to the management port.


The 2nd management port of the MRD 6000 can be configured from the web interface. To make changes to which port is the 2nd management port click, the configure control ports  button under the Unit Network Configuration section.

4.3.5 MPEG/IP Network Configuration

The MPEG/IP card is used to receive MPEG over IP transport streams. The MPEG/IP card supported unicast, multicast, UDP and RTP. The ports of the MPEG/IP card on the MRD 6000 can be configured from the web interface. To configure the Default Gateway and ICMP Response settings click the  **Configure Card** button.



Setting	Range	Description
Default Gateway	Port 1 Port 2	Setting to <i>Port 1</i> uses the gateway address of port 1 as the default gateway. Setting to <i>Port 2</i> uses the gateway address of port 2 as the default gateway.
ICMP Response	Enabled Disabled	Setting to enabled allows the MRD 6000 to respond to ICMP requests (ping). If disabled the MRD 6000 will not respond to these requests.

To configure the TCP/IP settings of the MPEG/IP ports click the  button under the MPEG/IP Network Configuration section next to the corresponding port. The settings for both ports are the same.

Configure MPEG/IP Slot 2 NIC 1

IP Address: 10.0.0.71

Subnet Mask: 255.255.255.0

Gateway: 0.0.0.0

Link Speed: Auto


Apply Cancel


Setting	Range	Description
IP Address	1.0.0.0 - 126.0.0.0 128.0.0.0 - 191.255.0.0 192.0.1.0 - 223.255.255.0	This setting is the TCP/IP address assigned to the port.
Subnet Mask	255.0.0.0 – 255.255.255.254	This setting is the subnet mask assigned to the port.
Gateway	1.0.0.0 - 126.0.0.0 128.0.0.0 - 191.255.0.0 192.0.1.0 - 223.255.255.0	This setting is the gateway address assigned to the port.
Link Speed	Auto 1000Mbps/Full 1000Mbps/Half 100Mbps/Full 100Mbps/Half 10Mbps/Full 10Mbps/Half	Setting Link Speed to Auto allows the MRD 6000 to determine the link speed of the network. If this is not possible or the user wants to define a link speed select one of the other values available.


4.3.6 Licensing

Certain features of the MRD 6000 require licenses in order to be functional. The interface displays all licenses available as well as the following status:

- License Locked or Unlocked
- License is Supported or Unsupported by the installed hardware


If licenses need to be applied to the MRD 6000 click  **Apply License Key** button. The menu below will appear where the user can copy and paste the provided license key from


Sencore. The currently applied license key can be viewed by clicking the  View Current Key button.



The dialog box titled "Enter License Key" features a large text input field with the placeholder text "Enter a new license key here...". At the bottom right, there are two buttons: "Apply" and "Cancel".

4.3.7 Date/Time


The MRD 6000 can be set to synchronize with an NTP server or a manual data and time can be defined by the user. Click the  Configure Date / Time button to configure the date and time. These values are used to timestamp entries in the Alarm and Event logs under the Reporting tab.



The dialog box titled "Configure Date / Time" contains the following fields:

- Update Mode:** A dropdown menu currently set to "Manual".
- NTP Server:** A text input field containing "0.0.0.0".
- Date:** A text input field containing "10/21/2012" with a calendar icon to its right.
- Time:** A text input field containing "14:34:00".

Below the input fields is a note: "Note: Changing time may prompt you to log-in." At the bottom right are "Apply" and "Cancel" buttons.

Setting	Range	Description
Update Mode	NTP Manual	Setting to <i>NTP</i> uses the local network's NTP server to synchronize date and time. <i>Manual</i> allows the user to define a date and time.
NTP Server	Four decimal octets: XXX.XXX.XXX.XXX Domain Name	This is the IP Address or Domain Name of the local NTP Server on the network. This setting is only available if Update Mode is set to NTP.
Date	MM/DD/YYYY	This setting is the user defined date. A calendar widget can be used to select the data by clicking the  button. This setting is only available if Update Mode is set to Manual.
Time	00:00:00 – 24:00:00	This setting is the user defined time. The time is based on a 24 hour clock. This setting is only


available if the Update Mode is set to Manual.

4.3.8 Configuring SNMP

4.3.8.1 SNMP Communities


SNMP Communities define whether users have read-only or read-write SNMP rights. These two communities are given unique names. The default names for these communities are:


- Read –Only Community: public
- Read- Write Community: private

To modify the names of these communities click on the  **Configure SNMP Communities** button.




4.3.8.2 SNMP Trap Managers

The SNMP trap managers are recipients of SNMP traps sent from the MRD 6000. The following menu allows the user to configure the recipient's IP addresses. To add and remove recipients of the SNMP traps click the  **Configure SNMP Managers** button.



Action	Button	Description
--------	--------	-------------

Add Manager

Clicking this button prompts the user for the IP address of the SNMP trap manager.


Delete All













Clicking this button prompts the user to confirm the deletion of all SNMP trap manager IP addresses. If the user confirms deletion all SNMP trap manager IP addresses will be removed.

Delete Single Entry

Highlight a single SNMP trap manager IP address and click this button to delete the entry. A prompt will appear confirming the deletion of IP address.

4.3.8.3 Download SNMP MIB Files


The MRD 6000 stores the SNMP MIB files for the currently installed version of software on the unit. These files can be downloaded directly from the MRD 6000 by clicking on the  button. The screen below will appear where the files can be downloaded and saved off of the unit.

Index of /mibs/				
Name	Last Modified	Size	Type	
Parent Directory/		-	Directory	
 INET-ADDRESS-MIB.MIB	2012-Oct-18 13:54:20	16.3K	application/octet-stream	
 SENCORE-CSP-MIB.MIB	2012-Oct-18 13:54:20	66.7K	application/octet-stream	
 SENCORE-GLOBAL-REG.MIB	2012-Oct-18 13:54:20	2.3K	application/octet-stream	
 SENCORE-MRD5800-MIB.mib	2012-Oct-18 13:54:21	136.0K	application/octet-stream	
 SNMP-COMMUNITY-MIB.MIB	2012-Oct-18 13:54:20	15.1K	application/octet-stream	
 SNMP-FRAMEWORK-MIB.MIB	2012-Oct-18 13:54:20	21.8K	application/octet-stream	
 SNMP-MPD-MIB.MIB	2012-Oct-18 13:54:20	5.3K	application/octet-stream	
 SNMP-TARGET-MIB.MIB	2012-Oct-18 13:54:20	22.2K	application/octet-stream	
 SNMP-USER-BASED-SM-MIB.MIB	2012-Oct-18 13:54:20	38.2K	application/octet-stream	
 SNMP-VIEW-BASED-ACM-MIB.MIB	2012-Oct-18 13:54:20	33.3K	application/octet-stream	
 SNMPv2-MIB.MIB	2012-Oct-18 13:54:20	28.6K	application/octet-stream	
 SNMPv2-SMI.MIB	2012-Oct-18 13:54:20	8.7K	application/octet-stream	
 SNMPv2-TC.MIB	2012-Oct-18 13:54:20	37.1K	application/octet-stream	

To Download: Right-Click, Save Link As or Save Target As

4.3.9 Syslog

The MRD 6000 can be configured to send error and event logs formatted in the syslog protocol to a remote user specified Syslog server.




The image shows a 'Configure Syslog' dialog box with the following fields:


- State: Enabled (dropdown menu)
- Network Protocol: UDP (dropdown menu)
- IP Address: 172.16.14.38 (text field)
- Port: 514 (text field)

Buttons: Apply, Cancel

Action	Range	Description
State	Enabled Disabled	Enable or Disable sending messages to Syslog server.
Network Protocol	UDP TCP	Select which network protocol used to transmit to the Syslog server
IP Address	Four decimal octets: XXX.XXX.XXX.XXX	IP of the Syslog server. 0.0.0.0 and 255.255.255.255 are not permitted
Port	0 - 65535	Destination port of the Syslog server

4.3.10 In-Band Control


The In-Band Control is used to change settings and receive updates from data within a PID in the incoming TS, as injected by the Sencore CMD 4000 In-band Control Server. The following menu allows the user to configure the In-Band Control settings. To configure the In-Band Control settings click the  **Configure In-Band Control** button.







Action	Range	Description
State	Enabled Disabled	Enable or Disable the In-Band Control.
PID	1-8190	Sets the unit to look for commands on the PID that is set.
Group	None 1-128	This setting assigns the unit to a corresponding Group or No Group.

4.3.11 Updating the MRD 6000

4.3.11.1 Applying Software Updates


Updates to the MRD 6000 are performed through the web interface. A software update file is provided by Sencore and then uploaded to the unit. Once uploaded, the software update is applied to the unit. To upload software updates to the unit click on the  **Update Unit** button. The current version and uploaded version is displayed in the Software Versions section. The MRD 6000 will reboot after a software update is complete.





Action	Button	Description
Upload Software Update		To upload software updates to the MRD 6000 click this button. The user will be prompted to navigate to an update file. The file will then upload to the MRD 6000. When complete the MRD 6000 will prompt the user to either apply the update or cancel
Delete the Uploaded Software		Clicking this button prompts the user to confirm the deletion of the software update from the MRD 6000. This will also clear the Uploaded Version status of the Software Versions section.
Update Software to Uploaded Version		Clicking the button starts the software update process. The MRD 6000 will prompt the user to confirm the update. Click Yes to continue or No to cancel.

4.3.11.2 Rollback Software Updates


The MRD 6000 is capable of reverting back to a previous version of software using the Rollback feature. The MRD 6000 maintains two separate software images; one is the most current version of software with all current settings and the other is the previous

version of software with all settings. To perform a rollback, click the  **Update Unit** button and then click the **Rollback** tab. The MRD 6000 will reboot after the rollback process is complete.




Action	Button	Description
Rollback Software		Clicking this button starts the Rollback process. The MRD 6000 will prompt the user to confirm the rollback or click cancel to stop the process.





4.3.12 Reboot Unit

The MRD 6000 can be rebooted from the web interface. In order to perform a reboot click the  **Reboot** button. The MRD 6000 will prompt the user to confirm the reboot. Once the reboot is complete the login screen will appear allowing the web interface to be logged into.

4.3.13 Reset Defaults

The MRD 6000 settings can be reset to factory defaults. All settings will be returned to the factory defaults except the network management ports TCP/IP settings. All event logs will be cleared. To reset all settings to default click the  **Reset to Defaults** button. The MRD 6000 will prompt the user to confirm the reset.





4.4 Reporting Panel

Main	Admin	Reporting	About
Reporting Control Panel			
Alarms	Logs	Configure	
State	Name	Location	Last Changed
	Transport Stream Not Present	Unit	12/17/2012 16:27:19
	Link Loss Error	MPEG/IP Slot 1 NIC 1	12/17/2012 16:27:31
	IP Loss Error	Input MPEG/IP 2-1	12/17/2012 16:27:36
	TS Sync Loss	Input MPEG/IP 2-1	12/17/2012 16:27:31



The **Reporting** tab in the MRD 6000 contains logs for active alarms currently affecting the unit and an event log. The active alarms are updated periodically in order to reflect the real-time state of the unit. Once an error is cleared it will be cleared from the active alarms window. The event log can be used to view alarm and event history. Both the active alarm and event logs can be configured to hide or change the behavior of alarms and events.

4.4.1 Active Alarms




Clicking on the **Alarms** button displays the Active Alarms menu. This list displays all of the active alarms currently affecting the unit. There are four columns in the log that display different types of information.










































Main	Admin	Reporting	About
Reporting Control Panel			
Alarms	Logs	Configure	
State	Name	Location	Last Changed
	Video Not Decoding	Decoder	12/17/2012 16:28:27
	Link Loss Error	MPEG/IP Slot 1 NIC 1	12/17/2012 16:28:45
	Link Loss Error	MPEG/IP Slot 1 NIC 2	12/17/2012 16:28:41
	Input Video Unsupported	Decoder	12/17/2012 16:28:27






Title	Description
-------	-------------

State	This column displays the nature of the alarm. The  icon means the log entry is informational and is not an error. The  icon means the log entry is an active alarm.
Name	This column displays the description of the error. The function that is experiencing an error condition is described here.
Location	This column displays the hardware or function that is experiencing the active error.
Last Changed	This column displays the data and time the error was raised. This data and time correlates with the Date and Time settings configured in Section 4.3.7.


4.4.2 Event Logs


Clicking on the  button displays the Event Log menu. This list displays all of the events and alarms that have affected the unit. The MRD 6000 stores up to four days' worth of logs. If the unit is rebooted or powered off and on the event logs are cleared. The logs can be cleared manually by clicking the  button. The logs can be downloaded as a .tsv file and saved to an external location by clicking the  button. There are five columns in the log that display different types of information.

Main Admin Reporting About				
Reporting Control Panel				
Alarms Logs				Configure
 				
Severity	Timestamp	Transition	Message	Location
	10/27/2012 17:48:41		Fan Recovered	Unit
	10/27/2012 17:48:36		Fan speed fp.1 below lower limit (0rpm)	Unit
	10/27/2012 17:34:51		Video Decoding	Decoder
	10/27/2012 17:34:49		Video Not Decoding	Decoder
	10/27/2012 17:33:06		Enabled CAM Present	Cam Slot 2
	10/27/2012 17:33:01		Enabled CAM Present	Cam Slot 1
	10/27/2012 17:31:39		Video Decoding	Decoder
	10/27/2012 17:30:47		Time Updated Via NTP [Offset by 0 seconds]	Unit
	10/27/2012 17:30:47		Time Updated Via NTP [Offset by 1351258624 seconds]	Unit
	01/02/1970 03:51:50		Transport Stream Present	Unit
	01/02/1970 03:51:50		Video Not Decoding	Decoder
	01/02/1970 03:51:50		ES Video Type Mismatched	Decoder
	01/02/1970 03:51:48		TS Sync OK	Input ASI
	01/02/1970 03:51:48		TS Sync OK	Input DVBS2 1-A
	01/02/1970 03:51:48		Receiver Locked	Input DVBS2 1-1
	01/01/1970 02:13:07		Transport Stream Not Present	Unit
	01/01/1970 02:13:06		Video Decoding	Decoder
Page 1 of 4 Severity:  Info  Error Transition:  Event  Went Good  Went Bad				



Title	Description
Severity	This column displays the nature of the alarm. The  icon means the log entry is informational and is not an error. The  icon means the log entry is an active alarm.
Timestamp	This column displays the data and time the error was raised or cleared. This data and time correlates with the Date and Time settings configured in Section 4.3.7.
Transition	This column displays when an alarm transition from a bad to good state. When an error is raised the  icon is displayed. When an error is cleared the  icon is displayed. When an event takes place the  icon is displayed.
Message	This column displays the description of the error or event. The function or hardware that experienced the event or error is described here.
Location	This column displays the hardware or function that experienced the alarm or event.

4.4.3 Configuring the Logs

The MRD 6000 allows the user to configure alarms and events. Events and alarms can be hidden, set to send SNMP traps or close a relay when active. In order to configure these options click the  **Configure** button while in the **Logs** section of the **Reporting** tab. The **Conditions** tab allows the user to configure the alarms reported by the MRD 6000. The **Events** tab allows the user to configure the events reported by the MRD 6000. Each column and its function are described below. A user configured time offset can also be applied to allow viewing the logs in a local time zone.




Name	Location	Log <input checked="" type="checkbox"/>	Severity	Alarm <input type="checkbox"/>	Relay <input type="checkbox"/>	Relay #
PID Filter Selection Not Present	PID Filter 4	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
PID Filter Selection Not Present	PID Filter 5	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
PID Filter Selection Not Present	PID Filter 6	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
PID Filter Selection Not Present	PID Filter 7	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
PID Filter Selection Not Present	PID Filter 8	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
PID Filter Selection Not Present	PID Filter 9	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
PID Not Present Condition	Audio 1	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
PID Not Present Condition	Audio 2	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
Selected PCR Pid Not Present	Decoder	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
Selected Video Pid Not Present	Decoder	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
Service Not Found	BISS	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
Service Not Found	Decoder	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
Temperature Error	Unit	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
Transport Error Indicator	Unit	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
Transport Stream Not Present	Unit	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
TS Sync Loss	Input ASI 1	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
TS Sync Loss	Input ASI 2	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1
Video Not Decoding	Primary Video Output	<input checked="" type="checkbox"/>	Error	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Relay 1

Title	Description
Name	This column displays the name of the error or condition. This is informational data: no options can be set here.
Location	This column displays the hardware or function that the alarm or event applies to. This is informational data; no options can be set here.
Log	Checking the box in this column creates an entry in the event log in the case this error or event is raised. If this box is unchecked this error or event will be hidden and not logged if raised.
Log Severity	This column is only available in the Conditions tab This option allows the user to set the severity of the error to Info or Error. If Info is selected in the drop down box the  icon will displayed in the event log. If Error is selected the  icon will be displayed in the event log.
Alarm	This column is only available in the Conditions tab This option allows the user to enable or disable this alarm in the Active Alarms log. If checked the alarm will be displayed in the Active Alarms log if raised. If this box is unchecked this error will be hidden.
SNMP Trap	This column allows the user to send an SNMP Trap if this alarm is raised. If this box is checked an SNMP Trap is sent when this alarm is raised. If this box is unchecked an SNMP is not sent.
Relay	This column allows the user to set a Relay closure if this alarm is raised. If this box is checked a Relay will be closed. If this box is unchecked a Relay will not be closed. See D for pinout
Relay #	This column allows the user to select which of the three relays available on the MRD 6000 will be closed when the alarm is raised.
Relay Duration	This column is only available in the Events tab. This option allows the user to define the length of time in milliseconds the relay will be closed after the event is logged. This setting can be configured from 100-1000 milliseconds.

4.5 About Panel

Under the **About** tab, is useful information about the unit software, serial number and licensing. There are no user definable parameters in the About panel. The Panel includes information about the unit software version currently installed, the unit serial and/or ID number, which licenses are installed, and how to contact Sencore. Information regarding third party software is available by clicking on the dropdown menu box.



4.6 System Recovery

The MRD 6000 has the ability to recover from a complete system software corruption. The system recovery allows a user to start the platform into a prompt where a software update will allow the system to be installed in the event all other images will not work.

To use the system recovery, push and hold two front panel pushbuttons (any 2 buttons) when power is applied to the unit. Hold the buttons for at least 20 seconds and then release.

The unit will boot into a recovery mode indicated by the front panel display and indicate a unit management IP address. The user can press the “Enter” button on the front panel to configure the IP address if necessary. A web browser can then be used to connect to the system and apply an update to the unit.

Section 5 Appendices



Introduction

This section includes the following appendices:

Appendix A	– Acronyms and Glossary	75
Appendix B	– Error and Event List	78
Appendix C	– Specifications	80
Appendix D	– Pinouts for Analog Audio and Relay Connectors	89
Appendix E	– MRD 6000 Audio Explanation	91
Appendix F	– MRD 6000 Discrete Audio Configuration	94
Appendix G	– Open Source Software	94
Appendix H	– Warranty	96
Appendix I	– Support and Contact Information	96

Appendix A – Acronyms and Glossary

8VSB: Vestigial sideband modulation with 8 discrete amplitude levels.

16VSB: Vestigial sideband modulation with 16 discrete amplitude levels.

AAC: Advanced Audio Coding

AC-3: Also known as Dolby Digital

AES: Audio Engineering Society

AFD: Auto Format Descriptor

ASI: Asynchronous Serial Interface

ATSC: Advanced Television Systems Committee

AV: Audio Video

Bit Rate: The rate at which the compressed bit stream is delivered from the channel to the input of a decoder.

BNC: British Naval Connector

BPS: Bits per second.

CAM: Conditional Access Module

CAT: Conditional Access Table

CAT6: Category 6 – Cable standard for gigabit Ethernet

CC: Closed Caption

CI: Common Interface

CoP: Code of Practice

CRC: Cyclic Redundancy Check

CVCT: Cable Virtual Channel Table

dB: Decibel

DDPlus: Dolby Digital Plus

DHCP: Dynamic Host Configuration Protocol

DPI: Digital Program Insertion

DTVCC: Digital Television Closed Captioning

DVB: Digital Video Broadcasting

EBU: European Broadcasting Union

EIA: Electronic Industries Alliance

EIT: Event Information Table

EPG: Electronic Program Guide

ETM: Extended Text Message

ETT: Extended Text Table

Event: An event is defined as a collection of elementary streams with a common time base, an associated start time, and an associated end time.

FCC: Federal Communications Commission

FEC: Forward Error Correction

Field: For an interlaced video signal, a “field” is the assembly of alternate lines of a frame. Therefore, an interlaced frame is composed of two fields, a top field and a bottom field.

Frame: A frame contains lines of spatial information of a video signal. For progressive video, these lines contain samples starting from one time instant and continuing through successive lines to the bottom of the frame. For interlaced video a frame consists of two fields, a top field and a bottom field. One of these fields will commence one field later than the other.

HANC: Horizontal Ancillary

HD: High Definition

High level: A range of allowed picture parameters defined by the MPEG-2 video coding specification which corresponds to high definition television.

I/O: Input/Output
IP: Internet Protocol
Kbps: 1000 bit per second
LED: Light Emitting Diode
LNB: Low-Noise Block
MAC: Medium Access Control
Main level: A range of allowed picture parameters defined by the MPEG-2 video coding specification with maximum resolution equivalent to ITU-R Recommendation 601.
Main profile: A subset of the syntax of the MPEG-2 video coding specification that is expected to be supported over a large range of applications.
Mbps: 1,000,000 bits per second.
MER: Modulation Error Ratio
MGT: Master Guide Table
MIB: Management Information Base
MP@HL: Main profile at high level.
MP@ML: Main profile at main level.
MPEG: Refers to standards developed by the ISO/IEC JTC1/SC29 WG11, *Moving Picture Experts Group*. MPEG may also refer to the Group.
MPEG-2: Refers to ISO/IEC standards 13818-1 (Systems), 13818-2 (Video), 13818-3 (Audio), 13818-4
MPTS: Multiprogram Transport Stream
MRD: Modular Receiver Decoder
NTP: Networking Time Protocol
NTSC: National Television System Committee
OSD: On Screen Display
PAL: Phase-Alternating Line
PAT: Program Association Table
PCM: Pulse-Code Modulation
PCR: Program Clock Reference
PCM: Pulse-code Modulation
PID: Packet Identifier. A unique integer value used to associate elementary streams of a program in a single or multi-program transport stream.
PMT: Program Map Table
Profile: A defined subset of the syntax specified in the MPEG-2 video coding specification
Program specific information (PSI): PSI consists of normative data which is necessary for the demultiplexing of transport streams and the successful regeneration of programs.
Program: A program is a collection of program elements. Program elements may be elementary streams. Program elements need not have any defined time base; those that do have a common time base and are intended for synchronized presentation.
PTS: Presentation Time Stamp
QAM: Quadrature Amplitude Modulation
QPSK: Quadrature Phase-Shift Keying
RDS: Receiver Decoder System
RF: Radio Frequency
RGBHV: Red, Green, Blue, Horizontal, Vertical
RO: Read Only
RPM: Revolutions Per Minute
RRT: Rating Region Table
RS-232: Recommended Standard. A standard for serial binary data interconnection.

RU: Rack Unit
RW: Read/Write
SD: Standard Definition
SDI: Serial Digital Interface
SFP: Small Form-Factor Pluggable
SI: System Information
SMPT: Society of Motion Pictures and Television Engineers
SNMP: Simple Network Management Protocol
SPTS: Single Program Transport Stream
SSRC: Synchronization Source
STD input buffer: A first-in, first-out buffer at the input of a system target decoder for storage of compressed data from elementary streams before decoding.
STD: System Target Decoder. A hypothetical reference model of a decoding process used to describe the semantics of the Digital Television Standard multiplexed bit stream.
STT: System Time Table
TS: Transport Stream
TVCT: Terrestrial Virtual Channel Table
UTC: Coordinated Universal Time
VANC: Vertical Ancillary
VBI: Video Blanking Interval
VCT: Virtual Channel Table. Used in reference to either TVCT or CVCT.
XLR: Cannon “X” series connector, with a Latch, and Rubber around the contacts.
YPbPr: Component Red, Green, Blue

Appendix B – Error and Event List

Error	Description
12V Supply Error	Voltage on 12V rail has exceeded safe operational range.
3.3V Supply Error	Voltage on 3.3V rail has exceeded safe operational range.
5V Supply Error	Voltage on 5V rail has exceeded safe operational range.
Audio Not Decoding	Audio is corrupted in incoming stream or format is not supported.
Auto Video Format Error	MRD 6000 is unable to determine the native incoming video in order to format output.
BISS Conflicting PIDs	PIDs selected to be descrambled by one BISS key are already assigned to be descrambled by another BISS key.
BISS Service Not Found	Service that BISS key is assigned to descramble is not present in the incoming stream.
Backup Input Active Condition	Primary input is currently in a failed condition and the MRD 6000 has failed over to the Backup input.
Bitrate Exceeded Error	Total incoming transport stream bitrate has exceeded 213 Mbps.
CAM Descramble Fail	CAM Module is not descrambling selected pids or services
CAM Not Present	DVB-CI Descrambling is enabled but CAM Module is not installed.
CAM PID Not Found	PID selected to be descrambled by the CAM is not present in the incoming stream.
ES Type Mismatch	Elementary stream type does not match the stream type defined by the user.
FEC Reception Error	Packets in incoming IP stream cannot be repaired with forward error correction.
Fan Speed Below Lower Limit	Cooling fan in the MRD 6000 has failed.
IP Loss Error	No IP packets have been received by the MPEG/IP card for two seconds.
ISI Not Found	ISI value defined by the user is not found in the incoming multistream signal.
Input Video Unsupported	Native format of incoming video is not a supported video format.
LNB Power Error	LNB Power is enabled but the MRD 6000 is detecting power is being provided by another source, there is excessive current drain or an overvoltage has occurred.
Link Loss Error	Physical IP link is not present on the MPEG/IP card.
Loss of Carrier Lock	Receiver carrier lock source is lost.
Low Level	8VSB/QAM RF Level is below the user settable threshold
Low Mer	8VSB/QAM MER is below the user settable threshold
Multistream Mode Input Mismatch	Multistream Mode is enabled and input signal is not multistream capable or Multistream Mode is disabled and input signal is multistream capable.

No Services Detected	Service Lock service selection mode is enabled but no services are present in the active input transport stream.
Pid Filter Overflow Error	Configured PID Filter TS rate is too low.
Pid Filter Selection Not Present	Selected Service or PID is not present for inclusion in the output PID filter TS.
RTP Reception Error	Uncorrectable out of order or duplicate packets are present in incoming IP stream.
ES Sync Error Condition	One of the in-use elementary streams is not synchronized to the PCR
Selected Audio PID Not Present	PID Locked mode is set as service selection mode and audio PID defined by user is not present in the incoming stream.
Selected PCR PID Not Present	PID Locked mode is set as service selection mode and PCR PID defined by user is not present in the incoming stream.
Selected Video PID Not Present	PID Locked mode is set as service selection mode and video PID defined by user is not present in the incoming stream.
Service Not Found	Service Lock service selection mode is enabled but service defined by user is not present in the incoming stream.
Temperature Error	The MRD 6000 has detected the internal temperature is 60 degrees Celsius or above.
Transport Error Indicator	The MRD 6000 has detected that the transport stream error indicator is present on the active input.
Transport Stream Not Present	The MRD 6000 has detected that the transport stream from the active input is no longer present.
TS Sync Loss	Transport stream sync for IP stream is not detected.
Unicast Receiver Not Found Error	The MRD 6000 cannot discover the destination for the unicast IP stream within 10 seconds after the initial ARP is sent.
Unlicensed Modulation	Input stream on active input is either 16APSK or 32APSK and the modulations are no licensed on the MRD 6000.
Unlicensed VCM/Multistream	Input stream on the active input contains a multistream signal and the MRD 6000 is not licensed for multistream.
Video Not Decoding	The configured service or video PID to be decoded is not being successfully decoded by the MRD 6000.

Appendix C - Specifications

MRD 6000 – Base Unit

Includes –	Display, keypad, embedded controller, chassis/case, power supply/line cord
System –	
Display Type:	LCD
Display Configuration:	240 pixels by 64 pixels
Keypad:	Snap-dome Membrane
Front Panel Lockout:	Password control, up to 8 alpha-numeric characters (no punctuations or spaces allows)
Configurations Allows:	Single video decoder with up to two option cards
Rear Panel:	Fixed inputs and outputs with two option card slots. Option cards not field upgradeable.
Remote Operation/Update Interface –	
Type:	Ethernet, 10/100
Rear Panels indicators:	Link (Green LED), Activity (Amber LED)
Connector:	RJ45
Front Panel Indicators –	
Error LED:	Red indicates error is occurring Off indicates no errors detected
INPUT LED:	Green indicates valid input is present Off indicates no valid input
Monitor and Control Interfaces –	
Web server GUI:	HTTP via web browsing for control & monitoring
Front Panel:	Control & monitoring
SNMP:	Control & monitoring
Operating Altitudes	0 to 10000 feet
AC Power –	
Operating Voltage:	100-240VAC
PSU Max Power:	150W
Current Draw:	Base Unit with no option cards – 38-40W MPEG/IP option card with active input – 2-3W (additional)
	DVB-S/S2 option card with active input and LNB load of 19V @ 500mA – 8-9W (additional)
	DVB-CI Module option with 2 CAM Modules installed – 2-3W (additional)
	8VSB/QAM option card with active input – 2-3W (additional)
Max Power Draw:	70-72W
Frequency:	48-63Hz
Connector:	IEC C14
Line Cord:	Detachable, 3-prong Base Unit with active ASI input – 54-55W

Video Decoding Features

General –

TS Data Rate: .25-200 Mb/s

Video Decoder –

Video Profiles and Levels:

Base Unit –

MPEG-2: to MP@HL,

H.264: to HP@L4.2

HEVC : to MP@HT up to L4.1, M10P@HT up to L4.1

Video Bit Rate:

MPEG-2 1-100Mb/s (dependent on profile)

H.264 CABAC Entropy coded 1 - 80Mb/s

CAVLC Entropy coded 1 - 100Mb/s

HEVC .25 – 40 Mbps

Video Formats:

Base Unit –

1080i x 1920 (16x9) @ 25, 29.97 and 30Hz

1080p x 1920 (16x9) @ 23.97, 24, 25, 29.97 and 30Hz

1080p x 1920 (16x9) @ 50, 59.94 and 60Hz

720p x 1280 (16x9) @ 50, 59.94, and 60Hz

576i x 720 (4x3 or 16x9) @ 25Hz

576i x 704 (4x3 or 16x9) @ 25hz

576i x 544 (4x3 or 16x9) @ 25hz

480i x 720 (4x3 or 16x9) @ 29.97Hz

4K/UHD Video Formats

Licensed formats (MRD 60730)

4096p x 2160 (16x9) 50, 59.94, and 60 Hz

4096p x 2160 (16x9) 23.98, 24, 25, 29.97, and 30 Hz

3840p x 2160 (16x9) 50, 59.94, and 60 Hz

3840p x 2160 (16x9) 23.98, 24, 25, 29.97, and 30 Hz

SDI (Serial Digital Interface) Video

Out –

SDI Standards:

Base Unit –

SD-SDI ANSI/SMPTE 259M

HD-SDI ANSI/SMPTE 292M

3G-SDI Level A ANSI/SMPTE 424M

Quad 3G-SDI SMPTE 425-3, SMPTE 425-5

Modes: Two Sample Interleave, Square Division

75Ω Female BNC (4x) (Ports: 1A, 2, 3, 4)

Connector:

Return Loss:

≥15 dB, 5Mhz to 1.5GHz

≥10 dB, 1.5 GHz to 3.0GHz

Drive Level:

800 mVpp ±10%

Data Bit Rate:

3G-SDI – 3.0 Gb/s

HD-SDI – 1.5 Gb/s

SD-SDI – 270Mb/s

Display Modes:

HD – Pillarbars, Cropped, Anamorphic

SD – Letterbox, Cropped, Anamorphic

Simultaneous SDI (Serial Digital

Interface) Video Out –

SDI Standards:

Mirrored 1x simultaneous output (Port 1 = Port 1B), Note:

When outputting 4K format (Two Sample Interleave) the

Simultaneous Output is a 1080p format of the 4K mode

Connector:

75Ω Female BNC

Return Loss:	≥15 dB, 5Mhz to 1.5GHz
Drive Level:	800 mVpp ±10%
Data Bit Rate:	SD-SDI – 270Mb/s
Display Modes:	16x9 – Pillarbox, Center-Cut, Anamorphic 4x3 – Letterbox, Center-Cut, Anamorphic

Composite Video Out –

Video Format Standards:	SMPTE 170M-2004, NTSC, PAL-B/G/I/D/M/N
Connector:	One 75 Ω ±10% Female BNC (CVBS)
Return Loss:	>25dB, 0 to 6.00 MHz
Frequency Response:	± 0.7dB From 0 to 4.00MHz
Drive Level:	140 IRE (1.0Vpp), ±2 IRE
Chroma/Luma Delay:	±26 ns Max
Field Time Distortion:	< 2% (± 3 IRE)
Line Time Distortion:	< 1% (± 1 IRE)
Short Time Distortion:	< 2% (± 3 IRE)
Differential Gain:	< 4%
Differential Phase:	< 1.5° degrees
Signal to Noise Ratio:	≥55dB luminance weighted
K factor	< 2.5%

Digital Video Out –

Digital Video Standard:	SDA-HDMI-OM-E Rev A
Connector:	HDMI-type Female Type-A

Audio Decoding Features

Number of Audio Services:	Base Unit – 2 Audio Services 4 Audio Service Decode License (MRD 66840) Adds – 2 Audio Services (4 total)
Audio Codecs Supported:	Dolby Digital (AC-3) & Plus (EAC-3) AAC-LC, HE-AAC, & HE-AACv2 MPEG1L2 & MPEG2L2 Linear PCM & Dolby E (Pass-through)
Output Formats:	Digital Pass-through PCM (Decoded Discrete channels for 5.1 sources or Downmixed for 5.1 Sources) Analog (Decoded Discrete channels for 5.1 sources or Downmixed for 5.1 Sources)

Audio Output Features

AES Outputs –	4x 75Ω BNC AES3/EBU Unbalanced
Analog Outputs –	
Output Type:	Balanced, 1 channel pairs (+/-, L/R)
Connector:	1x High density 15-pin D-sub, male
Impedance:	<100Ω Nominal Output Impedance
Max Output Level:	+24dBu @ 0dBfs Adjustable down to +10dBu by 0.5dB steps.
Conditions For Measurements	≥600Ω Load Impedance

THD+N:	-20dBFS encoded TS source
Dynamic Range:	Output level is adjusted to +4 dBu @ -20 dBFS
Signal to Noise	< 0.015% from 20 Hz to 20kHz @ +24dBu
Crosstalk:	104 dB
Frequency Response:	80 dB
Optional Breakout Cables:	< -80dB from 20Hz to 20kHz
	±0.5dB 20Hz to 20kHz,
	4x XLR Breakout Cable (MRD_AUD_OPT_XLR)
	4x BNC Breakout Cable (MRD_AUD_OPT_BNC)
	1x Terminal Block (MRD_AUD_OPT_TERM)
SDI Embedded Audio Output Standards:	
	SMPTE 272M (for SD-SDI)
	SMPTE 299 (for HD-SDI)
Density:	8 Audio Pairs
Sampling Frequency:	48 kHz

Ancillary Data Support

SDI VANC Data Types:	AFD (SMPTE 2016)
	Closed Captions (CEA-708)
	OP-47 (SMPTE RDD-08)
	SMPTE RDD-11
	TVG2X, AMOL-48/96 (SCTE-127)
	Teletext/WSS/VPS (SMPTE-2031)
	Time Code (SMPTE 12M-2)
	SMPTE2038
	Source ID
	SCTE104 (SMPTE 2010)
	VII (SMPTE RP-186)
SDI HANC Data Types:	Time Code (SMPTE 12M-2)
VBI Waveforms (SDI/Composite):	Line 21 Captions (CEA-608)
	TVG2X, AMOL-48/96 (SCTE-127)
	Teletext (EN300706)
	WSS (EN300294)
	VPS (EN300231))
	Timecode in VBI (SMPTE 12M-1)
Synchronization with video :	Frame Accurate

ASI Input and Output Features

General –	
Connector:	2x BNC, Female
Impedance:	75Ω
Return Loss:	≥15dB, 3.5 to 270 MHz
ASI Serial TS Input / Output –	
Number of ASI Inputs:	1
Number of ASI Outputs:	1 (non loop-through)
Standard:	EN50083-9 (V2:3/98) DVB ASI
Data Bit Rate:	270 Mb/s
Maximum TS Rate:	200 Mb/s
Minimum TS Rate:	250 Kb/s
Packet Sizes	Input: 188 and 204 bytes
	Output: 188 bytes
Modes Supported:	Burst, Byte

DVB-CI Descrambling Module Option

CAM Decryption –

General –

Compatibility Standard:	DVB-CI EN 50221
Number of CAM Slots:	2
Auto CAM insertion/removal detection:	Yes
CAM Usage:	Selectable, Enable/Disable
CAM Name Display:	Yes
Multicrypt Support:	Yes

Decryption Selection –

Elementary Stream types:	Video (MPEG2 & H264), Audio
Selection Modes:	Base Unit – Decoded Elementary Streams

Multi-Service Descrambling License (MRD 58991) Adds –

Individually selectable elementary streams

Maximum TS bitrate
CAS Supported –

DVB-CI – 100Mb/s
All major CA vendors supported

BISS Descrambling Option

Compatibility Standard:

DVB-CSA

Supported Modes:

Base Unit – None

BISS Descrambling License (MRD58921) Adds –
Mode 1, Mode E, Injected ID

No limitation to number of services descrambled per key

Multi-BISS descrambling using up to 12 keys

Maximum TS bitrate:

200 Mb/s

IP Input/Output Module Option

General –

Connector:	2x 10/100/1000 auto negotiate Base-T RJ-45 Ethernet Ports
------------	---

Receive –

Input Format:	UDP, RTP and RTP with extension headers Multicast and Unicast CBR, VBR, Null Stripped
Receiver Capability:	2 simultaneous MPEG over IP transport streams
FEC Receive:	Pro MPEG CoP3 SMPTE2022 Range: $L \cdot D \leq 100$ $1 \leq L \leq 20$ $4 \leq D \leq 20$ Annex B

Multicast Filtering:	Filters based on IP address
Buffer size:	1 - 4000 KB, or 1 – 4000ms, user configurable
Bitrate Range:	.25 – 200 Mb/s
Packets/IP Frame:	1-7 MPEG Packets/IP Frame
IGMP Compatibility:	Version 2 and 3

Transmit –

Output Format:	UDP and RTP
Bitrate Range:	.25 – 200 Mb/s
Packets/IP Frame:	1-7 MPEG Packets/IP Frame
Number of Outputs:	2 Mirrored TS – Unicast and/or Multicast
IP FEC Output (MRD58925) Adds – FEC:	Columns, Columns/Rows
FEC Transmit:	Pro MPEG CoP3 SMPTE2022 Range: $L \cdot D \leq 100$ $1 \leq L \leq 20$ $4 \leq D \leq 20$

DVB-S/S2/S2X Input Module Option**General –**

Frequency Range:	950 MHz – 2150 MHz
Number of inputs:	4 (A, B, C and D)
Connector:	F-81 Type, Female (4)
Impedance:	75 Ohms
Return Loss:	>9 dB
Separation:	>50 dB adjacent, >60 dB non-adjacent
RF frequency:	950 MHz to 2150 MHz in 100 kHz steps
Tuning:	Difference between Satellite frequency and LO frequency
Satellite frequency:	950 – 14500 MHz
LO frequency:	0 – 12000 MHz, with presets of 0, 5150, 9750, 10600, 10750 and 11250 MHz
Packet size:	188 bytes
Tuning Step Size:	125 kHz, maximum
Nyquist root filter roll-off factors:	.05, .10, .15, .20, .25, .35
RF Input Level:	-65 dBm to -25 dBm
Input RF Spectrum:	Normal/Inverted Auto Detect
PL Scrambling Codes supported:	0-262,141
Image Rejection:	>30dB
Noise Figure:	<15dB, maximum
Max TS Bitrate:	160 Mb/s
LNB Power and 22 kHz Tone –	
LNB Power	Off/13/14/18/19VDC @ >450mA
LNB voltage regulation:	± 4%
22 kHz Tone:	Off/On @ 650 mV (± 250 mV) peak-peak
DVB-S –	
Standard:	EN 300 421
FEC Code:	Conv. + Reed-Solomon
Modulation:	QPSK
Modulation/Coding supported:	CCM
Code rates:	1/2, 2/3, 3/4, 5/6, 7/8
QPSK Symbol rate:	0.5-60 MSym/s
DVB-S2 –	
Standard:	EN 302 307
Decoding type:	LDPC and BCH
Modulation:	QPSK, 8PSK
Modulation/Coding supported:	CCM
FEC Framing Type	Short frame size (16200), Normal frame size (64800)
Supported rates:	QPSK: 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10

Symbol rate:	8PSK: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10
Pilot:	0.5-60 MSym/s
DVB-S2 Advanced (MRD 58916) Adds –	On/Off Auto Detect
Modulation:	16APSK, 32APSK
Modulation/Coding:	VCM
Supported Rates:	16APSK: 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
	32APSK: 3/4, 4/5, 5/6, 8/9, 9/10
Symbol Rate:	0.5-60 MSym/s
Multistream reception:	Single ISI (stream specified)
ISSY:	Supported

DVB-S/S2 Input Module Option

General –

Frequency Range:	950 MHz – 2150 MHz
Number of inputs:	4 (A, B, C and D)
Connector:	F-81 Type, Female (4)
Impedance:	75 Ohms
Return Loss:	>9 dB
Separation:	>50 dB adjacent, >60 dB non-adjacent
RF frequency:	950 MHz to 2150 MHz in 100 kHz steps
Tuning:	Difference between Satellite frequency and LO frequency
Satellite frequency:	950 – 14500 MHz
LO frequency:	0 – 12000 MHz, with presets of 0, 5150, 9750, 10600, 10750 and 11250 MHz
Packet size:	188 bytes
Tuning Step Size:	125 kHz, maximum
Nyquist root filter roll-off factors:	.05, .10, .15, .20, .25, .35
RF Input Level:	-65 dBm to -25 dBm
AFC Tuning Range:	± .5 MHz in Standard and Wide mode (with SR ≤ 1 MSps)
	± 1 MHz in Standard and Wide mode (with SR 1 ≤ 2 MSps)
	± 1.5 MHz in Standard and Wide mode (with SR 2 ≤ 3 MSps)
	± 2 MHz in Standard and Wide mode (with SR 3 ≤ 4 MSps)
	± 2.5 MHz in Standard and Wide mode (with SR 4 ≤ 5 MSps)
	± 3 MHz in Standard mode (with SR ≥ 5 MSps)
	± 4 MHz in Wide mode (with SR 5 ≤ 6 MSps)
	± 5 MHz in Wide mode (with SR ≥ 6 MSps)
	Standard / Wide modes user selectable
Input RF Spectrum:	Normal/Inverted Auto Detect
PL Scrambling Codes supported:	0-262,141
Image Rejection:	>30dB
Noise Figure:	<15dB, maximum

Max TS Bitrate:	160 Mb/s
LNB Power and 22 kHz Tone –	
LNB Power	Off/13/14/18/19VDC @ >450mA
LNB voltage regulation:	± 4%
22 kHz Tone:	Off/On @ 650 mV (± 250 mV) peak-peak
DVB-S –	
Standard:	EN 300 421
FEC Code:	Conv. + Reed-Solomon
Modulation:	QPSK
Modulation/Coding supported:	CCM
Code rates:	1/2, 2/3, 3/4, 5/6, 7/8
QPSK Symbol rate:	0.5-60 MSym/s
DVB-S2 –	
Standard:	EN 302 307
Decoding type:	LDPC and BCH
Modulation:	QPSK, 8PSK
Modulation/Coding supported:	CCM
FEC Framing Type	Short frame size (16200), Normal frame size (64800)
Supported rates:	QPSK: 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 8PSK: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10
Symbol rate:	0.5-60 MSym/s
Pilot:	On/Off Auto Detect
DVB-S2 Advanced (MRD 58916) Adds –	
Modulation:	16APSK, 32APSK
Modulation/Coding:	VCM
Supported Rates:	16APSK: 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 32APSK: 3/4, 4/5, 5/6, 8/9, 9/10
Symbol Rate:	0.5-60 MSym/s
Multistream reception:	Single ISI (stream specified)
ISSY:	Supported

8VSB/QAM Input Module Option

General –	
Frequency Range:	50 MHz – 1000 MHz VHF/UHF (Ch2 – Ch69) CATV (Ch2 – Ch158) Off Air, FCC, IRC, HRC
Channel Plans:	1
Number of inputs:	F-Type, Female
Connector:	75 Ohms
Impedance:	-34dBmV to + 40dBmV (A74 Compliant)
Sensitivity:	8VSB, QAM-B
Modulation:	Range: 0dB to 40dB
MER:	Accuracy: +/- 2dB Low Limit Alarm: User Defined Entry
RF Level:	Range: -34dBmV to +40dBmV Accuracy: +/- 5dBmV Low Limit Alarm: User Defined Entry
QAM –	
Standard:	ITU Annex B/SCTE DVS-031
QAM Mode:	64 and 256
De-interleaver:	I=1-128, J=128/1
Nyquist Roll Off (Alpha):	12%, 18%
8VSB –	

Standard:	ATSC A/53E
Decoding Levels:	8
Nyquist Roll Off (Alpha):	11.5%

DVB-T2/C2/ISDB-T Input Module Option

General –

Frequency Range:	42 MHz – 1002 MHz
Number of inputs:	1
Connector:	F-Type, Female
Impedance:	75 Ohms
Sensitivity:	-34dBmV to + 40dBmV (A74 Compliant)
Modulation:	QPSK, 16QAM, 32QAM, 64QAM, 128QAM, 256QAM, 1024QAM, 4096QAM
MER:	Range: 0dB to 40dB Accuracy: +/- 2dB Low Limit Flag: User Defined
RF Level:	Range: -34dBmV to +40dBmV Accuracy: +/- 5dBmV Low Limit Flag: User Defined

Appendix D – Pinouts for Analog Audio and Relay Connectors



(DB-15) ANALOG AUDIO 1-2

PIN	CHANNEL	FUNCTION
1	Channel 1	Left +
2	Channel 1	Right +
3	Channel 2	Left +
4	Channel 2	Right +
5	--	--
6	Channel 1	Left -
7	Channel 1	Right -
8	Channel 2	Left -
9	Channel 2	Right -
10	--	--
11	--	Ground
12	--	Ground
13	--	Ground
14	--	Ground
15	--	Ground


(DB-15) ANALOG AUDIO 3-4

PIN	CHANNEL	FUNCTION
1	Channel 3	Left +
2	Channel 3	Right +
3	Channel 4	Left +
4	Channel 4	Right +
5	--	--
6	Channel 3	Left -
7	Channel 3	Right -
8	Channel 4	Left -
9	Channel 4	Right -
10	--	--
11	--	Ground
12	--	Ground
13	--	Ground
14	--	Ground
15	--	Ground




(DB-9) RELAY PINOUT		
PIN	RELAY	FUNCTION
1	Relay 1	Normally Open
2	Relay 1	Normally Closed
3	Relay 2	Common
4	Relay 3	Normally Open
5	Relay 3	Normally Closed
6	Relay 1	Common
7	Relay 2	Normally Open
8	Relay 2	Normally Closed
9	Relay 3	Common

**DB-15 Connector
(Male) Pin #'s**



**DB-9 Connector
(Female) Pin #'s**



Note: Relay functions shown represent the MRD in a powered-on state with no active alarms.

Appendix E – MRD 6000 Audio Explanation

Downmix Audio Setup

There are two primary modes of audio down mix operation for the MRD 6000 receiver/decoders. These settings only affect the signal if the digital output is set to PCM. It will also affect those embedded audio channels that are set to a PCM down mix. There are no gain changes or decoding if the digital or embedded outputs are set to Pass-through. The preset modes are Monitor (the default setting) and Transmission.

The first preset, Transmission, allows no changes by the customer. Transmission is intended to provide a limited dynamic range signal to drive a set top box or a transmitter. The Transmission mode does respond to dialog normalization data. It provides a gain boost of 11 dB and has compression to prevent the signal from overdriving a modulator. The 11dB gain boost is applied to the analog outputs, AES digital outputs set to PCM, and any embedded outputs set to PCM. It will not affect the gain of digital outputs or embedded outputs set to Pass-Through. It is intended to provide a similar audio level as a broadcast TV station signal through an RF modulator. The down mix includes the center and surrounds channels if they are present, and is represented as Lt/Rt. (left total, right total)

The second preset is Monitor. It has moderate processing, no gain boost and its down mix involves left and right channels only (Lo/Ro). The mode setting is Line as the default, but may be changed to RF, Custom 0 or Custom 1. In Line mode, the Dolby Dialog Normalization data is followed along with moderate processing. The default down mix setting for Monitor is Lo/Ro. The down mix may be changed to Lt/Rt or Lt/Rt/auto. Lt/Rt auto follows the embedded data in the stream if the producer has a preferred down mix. It will switch automatically between Lo/Ro and Lt/Rt depending on the data in the stream. If no mode is specified, the down mix will be Lt/Rt. In addition, the Dual Mono modes of operation may be selected. They will only have an effect if the stream is encoded as Dual Mono. Dual Left or Dual Right applies that signal to both left and right channels of the digital service, left and right channels of the analog outputs, and left and right channels of any embedded stream set to PCM. Selecting RF as the compression setting will add 11 dB of gain and the same processing as the Transmission mode to the analog outputs, AES digital outputs set to PCM, and any embedded outputs set to PCM.

There is an additional selection at the bottom of the Dolby setup pull-down menu. This allows selection between Professional Mode and Consumer Mode. In Professional Mode the built-in latency value is 32 msec for all formats. In Consumer Mode, this latency varies depending on the format. If you wish to monitor using a consumer receiver, you should choose Consumer Mode. The output sampling rate will always be 48 kHz, even in consumer. The Consumer/Pro identification bit will be set to Consumer. Normal operation in the air chain will use the Professional setting. This setting affects both Dolby Digital (AC-3) and Dolby Digital Plus.

If you want to run with no processing, choose Custom 1, Lo/Ro, and Dynamic Range disabled. This will still allow gain changes called for in the Dolby metadata via Dial-Norm settings in the stream.

Audio Output Settings

The digital audio services may be set to PCM (AES) or Pass-through (AES data) as an output. This applies to all available sources. The PCM setting will decode and automatically down mix an AC-3 or Dolby Digital Plus stream to two channels of AES audio. Pass-through simply passes thru the Dolby AC-3 data in an AES stream to be decoded by an external decoder such as the Dolby 568. Be aware the Dolby DP-568 is a professional decoder and always has a decoding latency of 32 msec. The older Dolby DP-564 has both professional and consumer modes of operation. If it identifies the Pro/Consumer ID bit as Professional, the latency will always be 32 msec. If it identifies the Pro/Consumer bit as Consumer, the latency will vary according to the format. Check the DP-564 manual for the actual latency values for Consumer mode. The analog channels can be assigned to any of the digital sources. The analog gain may be adjusted for the desired level. The gain setting does not affect the level of either the embedded audio or the digital services. A setting of +4 dBu provides an output of +4 dBu for a digital signal level of -20 dBFS. To check the audio output level, place the audio setup in Custom1 mode, down mix set to Lo/Ro, and the Dynamic Range disabled. This will remove any signal processing in the down mix. Set the digital service output being measured to PCM. A test stream of -20dBFS will output from the digital services as -20dBFS. If the analog channels are set to a gain setting of +4 dBu, the output should be +4 dBu plus or minus 0.5 dBu. The analog output level can be set in increments of 0.5 dBu from -10 dBu to +4 dBu referenced to a -20 dBFS digital input level. When you are setting the output levels it is suggested that an AC-3 stereo tone (2.0) be used as the source. Do not use a Dolby AC-3 5.1 tone source as your test signal. The five channels will down mix to a different level structure than a stereo signal depending on the down mix setting.

Downmix Reference Table

The following table is applicable for MPEG Audio (Mono and Stereo), Dolby Digital (Mono, Stereo and 5.1), Dolby Digital Plus (Mono, Stereo and 5.1) and AAC (Mono, Stereo and 5.1).

Incoming audio PID -->	Downmix Option	--> Output effect
Stereo	Lo/Ro	OUT = IN
Stereo	Lt/Rt (DS)	OUT = IN
Stereo	Lt/Rt (Auto)	OUT = IN
Stereo	Dual mono	OUT = IN
Stereo	Dual left	OUT L = OUT R = IN L
Stereo	Dual right	OUT L = OUT R = IN R
Mono	Lo/Ro	OUT L = OUT R = IN
Mono	Lt/Rt (DS)	OUT L = OUT R = IN
Mono	Lt/Rt (Auto)	OUT L = OUT R = IN
Mono	Dual mono	OUT L = OUT R = IN

Mono	Dual left	OUT L = OUT R = IN
Mono	Dual right	OUT L = OUT R = IN
5.1	Lo/Ro	OUT L = L + C + Ls OUT R = R + C + Rs (per ATSC A52)
5.1	Lt/Rt (DS)	OUT L = L + C – Ls - Rs OUT R = R + C + Ls +Rs (per ATSC A52)
5.1	Lt/Rt (Auto)	Lo/Ro or Lt/Rt depending on dolby metadata
5.1	Dual mono	OUT L = front left OUT R = front right
5.1	Dual left	OUT L = OUT R = IN Lo
5.1	Dual right	OUT L = OUT R = IN Ro

Appendix F – MRD 6000 Discrete Audio Configuration

The MRD 6000 currently does not offer a Discrete Audio mix option or license. This option is available on other Sencore receiver/decoders models and differs from a normal downmix in that it simply decodes selected audio channels rather than mixing multiple channels into 2 channels. Its primary use is for passing individual audio channels, such as in Dolby 5.1, to separate audio components and/or outputs. If you require this feature please contact Sencore for an alternative solution.

Appendix G – Open Source Software

The MRD 6000 includes:

Package	Version	License	Copyright
AT32 UC3B Software Framework	1.7.0	BSD	2009, Atmel Corporation
BaseX4JIT	4.0	GPL Version 3, 29 June 2007	2007-2009, Active Group, Inc
BusyBox	1.20.1	GPL Version 2, June 1991	Erik Anderson, et. al.
Cgicc	3.2.9	LGPL Version 2.9, June 2007	Stephen F. Booth
dfu-programmer	0.5.2	GPL Version 2, June 1991	Weston Schmidt
Dropbear	2012.55	MIT-like	2002-2008 Matt Johnston, et. al (see license)
E2fsprogs	1.41.9	GPL Version 2, June 1991	Theodore Ts'o
ethtool	2.6.34	GPL Version 2, June 1991	David Miller, et. al.
FamFamFam Silk Icons	013	Creative Commons Attribution 2.5	Mark James
FastDB	3.71	MIT-like	Konstantin Knizhnik
FCGI	2.4.6	FastCGI	Open Market, Inc
Iproute2	3.4.0	GPL Version 2, June 1991	Stephen Hemminger, Alexey Kuznetsov
Libusb	0.1.12	GPL Version 2.1, Feb 1999	Johannes Erdfelt, Thomas Sailer, Brad Hards
Lighttpd	1.4.23	BSD	2004, Jan Kneschke
Linux	2.6.30	GPL Version 2, June 1991	Linus Torvalds, et. Al.
Log4cpp	1.0	GPL Version 2.1 Feb 1999	Bastiann Bakker
Monit	5.1.1	GPL Version 3, 29 June 07	2010 Tildeslash Ltd.
Net-SNMP	5.7.1	BSD	1989, 1991, 1992 by Carnegie Mellon Univsty.
NTP	4.2.4p7	NTP License	1992-2009 David L. Mills

OpenSSL	1.0.1c	BSD-Like	1998-2008 The OpenSSL Project, 1995-1998
OProfile	0.9.7	GPL Version 2, June 1991	John Levon, Philippe Elie, et. al
PCRE	8.00	BSD	1997-2009 University of Cambridge, 2007-2008
POPT	1.14	MIT	1998 Red Hat Software
qDecoder	12.0.2	BSD	200-2012 Seungyoung Kim
Socket-CAN	1171	BSD-like, GPL Version 2, June 1991	2002-2007 Volkswagen Group Electronic Research
Spawn-FCGI	1.6.3	BSD	Jan Kneschke, Stefan Bahler
TCLAP	1.2.0	MIT	2003 Michael E Smoot
U-Boot	2009.11.1	GPL Version 2, June 1991	Wolfgane Denk, et. al.
USB-Utils	0.86	GPL Version 2, June 1991	Thomas Sailer, Johannes Erdfelt, David Brownell,
Zlib	1.2.3	Zlib/libpng License	1995-2005 Jean-loup Gailly and Mark Adler

Appendix H – Warranty

Sencore One-Year Warranty

Sencore warrants this instrument against defects from any cause, except acts of God and abusive use, for a period of 1 (one) year from date of purchase. During this warranty period, Sencore will correct any covered defects without charge for parts, labor, or recalibration.

Appendix I – Support and Contact Information

Returning Products for Service or Calibration

The MRD 6000 is a delicate piece of equipment and needs to be serviced and repaired by Sencore. Periodically it is necessary to return a product for repair or calibration. In order to expedite this process please carefully read the instructions below.

RMA Number

Before any product can be returned for service or calibration, an RMA number must be obtained. In order to obtain a RMA number, use the following steps:

1. Contact the Sencore service department by going online to www.sencore.com and select Support.
2. Select Service and Repair from the options given.
3. Fill in the following required information:
 - a. First & Last Name
 - b. Company
 - c. Email
 - d. Phone Number
 - e. Ship and Bill to Address
 - f. Unit Model and Serial Numbers
4. A RMA number will be emailed you shortly after completing the form with return instructions.

Shipping the Product

Once an RMA number has been issued, the unit needs to be packaged and shipped back to Sencore. It's best to use the original box and packaging for the product but if this not available, check with the customer service representative for the proper packaging instructions.

Note: DO NOT return any power cables or accessories unless instructed to do so by the customer service representative

